

BELL EQUIPMENT GUMMIHJULSLÆSSERE L L2106D JOHN DEERE POWERTECH 6081H



MOTOR John Deere PowerTech 6081H
Kapacitet: 25 liter

ANVEND

Normalt, svovlniveau i brændstof <0,5 %

KLIMA

Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3

Multifleet SHPD 10W-40

Skift alle 500 timer

DIFFERENTIALE BAG

Kapacitet: 28,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Skift alle 3000 timer

DIFFERENTIALE FOR

Kapacitet: 28,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Skift alle 3000 timer

GEAR ZF 4WG210 4/3

Kapacitet: 26 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Skift alle 1000 timer

HYDRAULISK SYSTEM

Kapacitet: 117,5 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Skift alle 3000 timer

BELL EQUIPMENT GUMMIHJULSLÆSSERE L L2106D JOHN DEERE POWERTECH 6081H



SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 30,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.