

BELL EQUIPMENT LEDDELTE LASTBILER & TRÆKKERE 1766CL (4X4) ADE 366T



MOTOR ADE/Mercedes-Benz 366T
Kapacitet: 20 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40	Armado Synth 5W-30

Skift alle 250 timer/ 6 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40	Armado Synth 5W-30

Skift alle 100 timer

DRIVAKSLER Bell

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
Unigear LS GL-3/GL-5 85W-140		

Skift alle 1000 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Skift alle 1000 timer

GEAR Allison MD3560P 6/1
Kapacitet: 18 liter (Servicepåfyldning), Kapacitet: 28 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Matic 2032		

Skift alle 1000 timer

BELL EQUIPMENT LEDDELTE LASTBILER & TRÆKKERE 1766CL (4X4) ADE 366T



REDUKTIONSGEARKASSE 9100

Kapacitet: 4,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Matic 2032		

Skift alle 1000 timer

HYDRAULISK SYSTEM

Kapacitet: 80 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Perlus H 46	Perlus H 68	Perlus AF 46

Skift alle 2000 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Matic 2032	ATF Almirol	Perlus H 32

Skift alle 2000 timer

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 47 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant SP 15+	Coolant SP 12	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.