

BELL EQUIPMENT LEDDELTE LASTBILER & TRÆKKERE 2406D MK VI (4X4)



MOTOR Mercedes-Benz
Kapacitet: 29 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agrisynth LSP 10W-40	Armado Synth 10W-40	

Kontroller alle 10 timer, skift alle 500 timer

DIFFERENTIALE BAG
Kapacitet: 40 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Skift alle 2000 timer

DIFFERENTIALE FOR
Kapacitet: 40 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Skift alle 2000 timer

GEAR
Kapacitet: 30 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Matic 2032		

Skift alle 2000 timer

NAVREDUKTIONER BAG
Kapacitet: 2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Skift alle 2000 timer

BELL EQUIPMENT LEDDELTE LASTBILER & TRÆKKERE 2406D MK VI (4X4)



NAVREDUKTIONER FOR

Kapacitet: 2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Skift alle 2000 timer

REDUKTIONSGEARKASSE

Kapacitet: 4,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 2032

Skift alle 2000 timer

HYDRAULISK SYSTEM

Kapacitet: 70 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF-F (Ford)

Skift alle 4000 timer

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 28 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Skift alle 2000 timer

BELL EQUIPMENT LEDDELTE LASTBILER & TRÆKKERE 2406D MK VI (4X4)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.