

BELL EQUIPMENT LEDDELTE LASTBILER & TRÆKKERE 4206D MK V (4X4) MERCEDES-BENZ OM501LA



MOTOR Mercedes-Benz OM501LA
Kapacitet: 28 liter (Servicepåfyldning), Kapacitet: 34 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agrisynth LSP 10W-40	Armado Synth 10W-40	

Skift alle 500 timer

DIFFERENTIALE BAG Bell 25T
Kapacitet: 45 liter (Servicepåfyldning), Kapacitet: 46 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
Unigear LS GL-3/GL-5 85W-140		

Kontroller alle 1000 timer, skift alle 2000 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Kontroller alle 1000 timer, skift alle 2000 timer

DIFFERENTIALE BAG (VÅDSKIVEBREMSE) Bell

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Agrifluid HT-Plus

BELL EQUIPMENT LEDDELTE LASTBILER & TRÆKKERE 4206D MK V (4X4) MERCEDES-BENZ OM501LA



DIFFERENTIALE FOR Bell 25T
Kapacitet: 45 liter (Servicepåfyldning), Kapacitet: 46 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
Unigear LS GL-3/GL-5 85W-140		

Kontroller alle 1000 timer, skift alle 2000 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Kontroller alle 1000 timer, skift alle 2000 timer

DIFFERENTIALE FORAN (VÅDSKIVEBREMSER) Bell

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Agrifluid HT-Plus

GEAR Allison HD4060 6/1
Kapacitet: 34 liter (Servicepåfyldning), Kapacitet: 40 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Matic 2032		

Kontroller alle 500 timer, skift alle 2000 timer

REDUKTIONSGEARKASSE VGR 17000
Kapacitet: 4,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Matic 2032		

Skift alle 2000 timer

BELL EQUIPMENT LEDDELTE LASTBILER & TRÆKKERE 4206D MK V (4X4) MERCEDES-BENZ OM501LA

**SLUTDREV**

Kapacitet: 6,3 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Unigear LS GL-3/GL-5 85W-140*Kontroller alle 1000 timer, skift alle 2000 timer*

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90*Kontroller alle 1000 timer, skift alle 2000 timer***HYDRAULISK SYSTEM**

Kapacitet: 185 liter (Hydrauliksystem inkl. tank), Kapacitet: 177,6 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 30

PRODUKTANBEFALING 2

Multifleet SCD 10W*Skift alle 4000 timer***SMØREPUNKTER/NIPLER**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2**KØLESYSTEM**

Kapacitet: 33,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.