

# BELL EQUIPMENT LEDDELTE LASTBILER MED TIPPELAD B-C-D-E SERIES B18D MK 7 (6X4) MERCEDES-BENZ OM906LA (STAGE



**Motor** Mercedes-Benz OM906LA  
Kapacitet: 29 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Agrisynth LSP 10W-40**

PRODUKTANBEFALING 2

**Armado Synth 10W-40**

*Skift alle 500 timer*

**DIFFERENTIALE BAG 14R8E**

Kapacitet: 26 liter (Servicepåfyldning), Kapacitet: 27 liter (Tør efterfyld)

ANVEND  
Normal

KLIMA  
Middelhavsagtigt

PRODUKTANBEFALING 1

**Unigear LS GL-3/GL-5 85W-140**

*Kontroller alle 1000 timer, skift alle 2000 timer*

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Gearlube LS 80W-90**

*Kontroller alle 1000 timer, skift alle 2000 timer*

**DIFFERENTIALE FOR 14R8E**

Kapacitet: 29 liter (Servicepåfyldning), Kapacitet: 30 liter (Tør efterfyld)

ANVEND  
Normal

KLIMA  
Middelhavsagtigt

PRODUKTANBEFALING 1

**Unigear LS GL-3/GL-5 85W-140**

*Kontroller alle 1000 timer, skift alle 2000 timer*

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Gearlube LS 80W-90**

*Kontroller alle 1000 timer, skift alle 2000 timer*

# BELL EQUIPMENT LEDDELTE LASTBILER MED TIPPELAD B-C-D-E SERIES B18D MK 7 (6X4) MERCEDES-BENZ OM906LA (STAGE



**GI:AR** Allison 3000P ORS 6/1  
Kapacitet: 24 liter (Servicepåfyldning), Kapacitet: 36 liter (Tør efterfyld)

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1  |  |  |
|----------------------|--|--|
| <b>SP Matic 2032</b> |  |  |

*Skift alle 2000 timer*

**REDUKTIONSGEARKASSE** VGR 13100  
Kapacitet: 4,5 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1  |  |  |
|----------------------|--|--|
| <b>SP Matic 2032</b> |  |  |

*Skift alle 2000 timer*

**SLUTDREV**  
Kapacitet: 4 liter

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

| PRODUKTANBEFALING 1                 |  |  |
|-------------------------------------|--|--|
| <b>Unigear LS GL-3/GL-5 85W-140</b> |  |  |

*Kontroller alle 1000 timer, skift alle 2000 timer*

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1       |  |  |
|---------------------------|--|--|
| <b>Gearlube LS 80W-90</b> |  |  |

*Kontroller alle 1000 timer, skift alle 2000 timer*

**HYDRAULISK SYSTEM**  
Kapacitet: 70 liter (Hydrauliktank)

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 | PRODUKTANBEFALING 3 |
|---------------------|---------------------|---------------------|
| <b>Perlus H 46</b>  | <b>Perlus H 32</b>  | <b>Perlus H 68</b>  |

*Skift alle 4000 timer*

# BELL EQUIPMENT LEDDELTE LASTBILER MED TIPPELAD B-C-D-E SERIES B18D MK 7 (6X4) MERCEDES-BENZ OM906LA (STAGE



## SMØREPUNKTER/NIPLER

|        |                  |
|--------|------------------|
| ANVEND | KLIMA            |
| Normal | Middelhavsagtigt |

|                      |                                 |                              |
|----------------------|---------------------------------|------------------------------|
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                         |  |  |
|-------------------------|--|--|
| PRODUKTANBEFALING 1     |  |  |
| <b>Gear Grease EP 1</b> |  |  |

|        |       |
|--------|-------|
| ANVEND | KLIMA |
| Normal | Koldt |

|                         |  |  |
|-------------------------|--|--|
| PRODUKTANBEFALING 1     |  |  |
| <b>Gear Grease EP 0</b> |  |  |

## KØLESYSTEM

Kapacitet: 28 liter

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                       |                      |  |
|-----------------------|----------------------|--|
| PRODUKTANBEFALING 1   | PRODUKTANBEFALING 2  |  |
| <b>Coolant SP 15+</b> | <b>Coolant SP 12</b> |  |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.