

BELL EQUIPMENT LEDDELTE LASTBILER MED TIPPELAD B-C-D-E SERIES B20D MK II (6X4) MERCEDES-BENZ OM906LA (TIER 2)



MOTOR Mercedes-Benz OM906LA
Kapacitet: 29 liter (Servicepåfyldning), Kapacitet: 38 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Agrisynth LSP 10W-40	Armado Synth 10W-40

Skift alle 500 timer

DIFFERENSIAL MIDT Bell 14T
Kapacitet: 40 liter (Servicepåfyldning), Kapacitet: 48 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	
Unigear LS GL-3/GL-5 85W-140	

Kontroller alle 1000 timer, skift alle 2000 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	
Gearlube LS 80W-90	

Kontroller alle 1000 timer, skift alle 2000 timer

DIFFERENTIALE FOR Bell 14T
Kapacitet: 40 liter (Servicepåfyldning), Kapacitet: 48 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	
Unigear LS GL-3/GL-5 85W-140	

Kontroller alle 1000 timer, skift alle 2000 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	
Gearlube LS 80W-90	

Kontroller alle 1000 timer, skift alle 2000 timer

BELL EQUIPMENT LEDDELTE LASTBILER MED TIPPELAD B-C-D-E SERIES B20D MK II (6X4) MERCEDES-BENZ OM906LA (TIER 2)



GEAR ZF 6HP592C 6/1

Kapacitet: 10-15 liter (Servicepåfyldning), Kapacitet: 30 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 2032

Kontroller alle 500 timer, skift alle 2000 timer

REDUKTIONSGEARKASSE VGR 13200

Kapacitet: 4,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 2032

Skift alle 2000 timer

SLUTDREV

Kapacitet: 2 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Unigear LS GL-3/GL-5 85W-140

Kontroller alle 1000 timer, skift alle 2000 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 1000 timer, skift alle 2000 timer

BELL EQUIPMENT LEDDELTE LASTBILER MED TIPPELAD B-C-D-E SERIES B20D MK II (6X4) MERCEDES-BENZ OM906LA (TIER 2)



HYDRAULISK SYSTEM

Kapacitet: 70 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Perlus H 46

PRODUKTANBEFALING 2

Perlus H 68

PRODUKTANBEFALING 3

Perlus AF 46

Skift alle 4000 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 2032

PRODUKTANBEFALING 2

ATF Almirol

PRODUKTANBEFALING 3

Perlus H 32

Skift alle 4000 timer

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 28 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.