

BELL EQUIPMENT LEDDELTE LASTBILER MED TIPPELAD B-C-D-E SERIES B30C (6X6) ADE 442N



MOTOR Mercedes-Benz OM442N
Kapacitet: 30 liter, Filterkapacitet: 3,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40	Armado Synth 5W-30

Skift alle 250 timer/ 6 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40	Armado Synth 5W-30

Skift alle 100 timer

DRIVAKSLER Bell
Kapacitet: 40 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
Unigear LS GL-3/GL-5 85W-140		

Kontroller alle 250 timer, skift alle 2000 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Kontroller alle 250 timer, skift alle 2000 timer

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1		
Unigear LS GL-3/GL-5 85W-140		

Skift alle 100 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Skift alle 100 timer

BELL EQUIPMENT LEDDELTE LASTBILER MED TIPPELAD B-C-D-E SERIES B30C (6X6) ADE 442N



GEAR ZF 6WG210 6/3

Kapacitet: 16 liter (Servicepåfyldning), Kapacitet: 26 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 2

Multifleet SHPD 15W-40

PRODUKTANBEFALING 3

SP Matic 2032

Skift alle 1000 timer

SLUTDREV

Kapacitet: 2 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Unigear LS GL-3/GL-5 85W-140

Kontroller alle 250 timer, skift alle 2000 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 250 timer, skift alle 2000 timer

ANVEND

Første Service

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Unigear LS GL-3/GL-5 85W-140

Skift alle 100 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Skift alle 100 timer

BELL EQUIPMENT LEDDELTE LASTBILER MED TIPPELAD B-C-D-E SERIES B30C (6X6) ADE 442N



HYDRAULISK SYSTEM

Kapacitet: 80 liter (Hydrauliktank)

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Perlus H 46	Perlus H 68	Perlus AF 46

Skift alle 2000 timer

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Matic 2032	ATF Almirol	Perlus H 32

Skift alle 2000 timer

HYDRAULISK BREMSESYSTEM

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Perlus H 46	Perlus H 68	Perlus AF 46

Skift alle 4000 timer

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Matic 2032	ATF Almirol	Perlus H 32

Skift alle 4000 timer

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 38 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant SP 15+	Coolant SP 12	

Skift alle 2000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

PRODUKTANBEFALING

BELL EQUIPMENT LEDDELTE LASTBILER MED TIPPELAD B-C-D-E SERIES B30C (6X6) ADE 442N



advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.