

# BELL EQUIPMENT LEDDELTE LASTBILER MED TIPPELAD B-C-D-E SERIES B30L MK II (4X4) 1015 DEUTZ BF6M1015



**MOTOR** Deutz BF6M-1015  
Kapacitet: 29 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Agrisynth LSP 10W-40**

PRODUKTANBEFALING 2

**Armado Synth 10W-40**

*Skift alle 500 timer*

## DIFFERENTIALE BAG Bell

ANVEND  
Normal

KLIMA  
Middelhavsagtigt

PRODUKTANBEFALING 1

**Gear Oil Alcat 50**

*Kontroller alle 1000 timer, skift alle 2000 timer*

ANVEND  
Første Service

KLIMA  
Middelhavsagtigt

PRODUKTANBEFALING 1

**Gear Oil Alcat 50**

*Skift alle 100 timer*

## DIFFERENTIALE FOR Bell

ANVEND  
Normal

KLIMA  
Middelhavsagtigt

PRODUKTANBEFALING 1

**Gear Oil Alcat 50**

*Kontroller alle 1000 timer, skift alle 2000 timer*

ANVEND  
Første Service

KLIMA  
Middelhavsagtigt

PRODUKTANBEFALING 1

**Gear Oil Alcat 50**

*Skift alle 100 timer*

# BELL EQUIPMENT LEDDELTE LASTBILER MED TIPPELAD B-C-D-E SERIES B30L MK II (4X4) 1015 DEUTZ BF6M1015



## GEAR ZF 6WG210 6/3

Kapacitet: 16 liter (Servicepåfyldning), Kapacitet: 26 liter (Tør efterfyld)

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1  |  |  |
|----------------------|--|--|
| <b>SP Matic 2032</b> |  |  |

Skift alle 1000 timer

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

| PRODUKTANBEFALING 1  |  |  |
|----------------------|--|--|
| <b>SP Matic 2032</b> |  |  |

Skift alle 100 timer

## HYDRAULISK SYSTEM

Kapacitet: 85 liter (Hydrauliktank)

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 | PRODUKTANBEFALING 3 |
|---------------------|---------------------|---------------------|
| <b>Perlus H 46</b>  | <b>Perlus H 68</b>  | <b>Perlus AF 46</b> |

Skift alle 4000 timer

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2 | PRODUKTANBEFALING 3 |
|----------------------|---------------------|---------------------|
| <b>SP Matic 2032</b> | <b>ATF Almirol</b>  | <b>Perlus H 32</b>  |

Skift alle 4000 timer

## SMØREPUNKTER/NIPLER

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
|----------------------|---------------------------------|------------------------------|
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

## KØLESYSTEM

Kapacitet: 34 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1   | PRODUKTANBEFALING 2  |  |
|-----------------------|----------------------|--|
| <b>Coolant SP 15+</b> | <b>Coolant SP 12</b> |  |

Skift alle 2000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products.

# **BELL EQUIPMENT LEDDELTE LASTBILER MED TIPPELAD B-C-D-E SERIES B30L MK II (4X4) 1015 DEUTZ BF6M1015**



*Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*