

BELL EQUIPMENT LEDDELTE LASTBILER MED TIPPELAD B-C-D-E SERIES B30L MK III (4X4) CUMMINS QSM11



MOTOR Cummins QSM11
Kapacitet: 37 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2
Armado Synth 5W-30

PRODUKTANBEFALING 3
Dieselfleet CD+ 15W-40

Skift alle 250 timer/ 6 måneder

DIFFERENTIALE BAG Bell

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Gear Oil Alcat 50

Kontroller alle 1000 timer, skift alle 2000 timer

DIFFERENTIALE FOR Bell

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Gear Oil Alcat 50

Kontroller alle 1000 timer, skift alle 2000 timer

GEAR ZF 6WG210 6/3
Kapacitet: 16 liter (Servicepåfyldning), Kapacitet: 26 liter (Tør efterfyld)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Matic 2032

Skift alle 1000 timer

BELL EQUIPMENT LEDDELTE LASTBILER MED TIPPELAD B-C-D-E SERIES B30L MK III (4X4) CUMMINS QSM11



HYDRAULISK SYSTEM

Kapacitet: 140 liter (Hydrauliktank)

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Perlus H 46	Perlus H 68	Perlus AF 46

Skift alle 2000 timer

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Matic 2032	ATF Almirol	Perlus H 32

Skift alle 2000 timer

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 86 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Skift alle 2000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.