

BELL EQUIPMENT TRAKTORER 1226AF MKIII JOHN DEERE 6068TF150



MOTOR John Deere 6068 TF150
Kapacitet: 19 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Agridiesel MSP 15W-40

PRODUKTANBEFALING 2

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Skift alle 250 timer/ 6 måneder

DIFFERENTIALE BAG
Kapacitet: 32 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 250 timer, skift alle 1000 timer

DIFFERENTIALE FOR
Kapacitet: 10 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 250 timer, skift alle 1000 timer

GEAR Allison 2500 TC211 5/1
Kapacitet: 16,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Matic 2032

Kontroller alle 250 timer, skift alle 1000 timer

REDUKTIONSGEARKASSE Bell
Kapacitet: 4 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 250 timer, skift alle 1000 timer

BELL EQUIPMENT TRAKTORER 1226AF MKIII JOHN DEERE 6068TF150



HYDRAULISK SYSTEM

Kapacitet: 147 liter (Hydrauliksystem inkl. tank)

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Perlus H 68

PRODUKTANBEFALING 2

Perlus AF 68

Kontroller alle 250 timer, skift alle 3000 timer

SMØREPUNKTER/NIPLER HJULLEJER + DRIVANORDNING

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 19 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Skift alle 24 måneder/ 3000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.