

BELL EQUIPMENT

TREHJULSLÆSSERE/SKOVMASKINER

225E DEUTZ F4L912



MOTOR Deutz F4L-912
Kapacitet: 9 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

PRODUKTANBEFALING 3

Dieselfleet CD+ 15W-40

Skift alle 250 timer/ 6 måneder

HOVEDDREV

Kapacitet: 1,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 250 timer, skift alle 1000 timer

SLUTDREV

Kapacitet: 5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 250 timer, skift alle 1000 timer

HYDRAULISK SYSTEM

Kapacitet: 118 liter (Hydrauliksystem inkl. tank), Kapacitet: 105 liter (Hydrauliktank)

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1

Perlus H 68

Skift alle 3000 timer

SMØREPUNKTER/NIPLER

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

BELL EQUIPMENT

TREHJULSLÆSSERE/SKOVMASKINER

225E DEUTZ F4L912



BREMSESISTEM VÅDE BREMSER MED FLERE SKIVER

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Kroontrak CVT 10W-40

Skift alle 1000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.