

BOBCAT GRAVEMASKINER 442 (2002-2009)



MOTOR Deutz BF4M-2011		
ANVEND		KLIMA
Normal		Tropisk
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Multifleet SHPD 20W-50	Multifleet SCD 40	
<i>Kontroller alle 10 timer, skift alle 500 timer</i>		
ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1		
Multifleet SCD 30		
<i>Kontroller alle 10 timer, skift alle 500 timer</i>		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40
<i>Kontroller alle 10 timer, skift alle 500 timer</i>		
ANVEND		KLIMA
Normal		Koldt
PRODUKTANBEFALING 1		
Multifleet SCD 10W		
<i>Kontroller alle 10 timer, skift alle 500 timer</i>		
ANVEND		KLIMA
Første Service		Tropisk
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Multifleet SHPD 20W-50	Multifleet SCD 40	
<i>Kontroller alle 10 timer, skift alle 100 timer</i>		
ANVEND		KLIMA
Første Service		Middelhavsagtigt
PRODUKTANBEFALING 1		
Multifleet SCD 30		
<i>Kontroller alle 10 timer, skift alle 100 timer</i>		
ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40
<i>Kontroller alle 10 timer, skift alle 100 timer</i>		

BOBCAT GRAVEMASKINER 442 (2002-2009)



ANVEND		KLIMA
Første Service		Koldt
PRODUKTANBEFALING 1		
Multifleet SCD 10W		
<i>Kontroller alle 10 timer, skift alle 100 timer</i>		

KØREREDUKTIONSENHED KOMBINERET MED HYDRAULIKSYSTEM Kapacitet: 1,8 liter		
ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1		
Perlus AF 100		
<i>Kontroller alle 250 timer, skift alle 6 måneder/ 1000 timer</i>		

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Perlus H 46	Perlus H 68	Perlus AF 46
<i>Kontroller alle 250 timer, skift alle 6 måneder/ 1000 timer</i>		

ANVEND		KLIMA
Første Service		Middelhavsagtigt
PRODUKTANBEFALING 1		
Perlus AF 100		
<i>Skift alle 100 timer</i>		

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Perlus H 46	Perlus H 68	Perlus AF 46
<i>Skift alle 100 timer</i>		

ANVEND		KLIMA
Alternativ (acceptabel)		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Kroontrak MTH 10W-30	HDX 10W	
<i>Kontroller alle 250 timer, skift alle 6 måneder/ 1000 timer</i>		

ANVEND		KLIMA
Startservice (alternativ)		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Kroontrak MTH 10W-30	HDX 10W	
<i>Skift alle 100 timer</i>		

BOBCAT GRAVEMASKINER 442 (2002-2009)



KØREREDUKTIONSENHED SEPARAT SMØRING

Kapacitet: 1,8 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 200 timer, skift alle 1000 timer/ 12 måneder

HYDRAULISK SYSTEM

Kapacitet: 110 liter (Hydrauliktank), Kapacitet: 140 liter (System)

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1		
Perlus AF 100		

Kontroller alle 10 timer, skift alle 6 måneder/ 1000 timer

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Perlus H 46	Perlus H 68	Perlus AF 46

Kontroller alle 10 timer, skift alle 6 måneder/ 1000 timer

ANVEND		KLIMA
Alternativ (acceptabel)		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Kroontrak MTH 10W-30	HDX 10W	

Kontroller alle 10 timer, skift alle 6 måneder/ 1000 timer

ANVEND		KLIMA
Biologisk nedbrydelig olie		Moderat
PRODUKTANBEFALING 1		
Perlus Biosynth 46		

Kontroller alle 10 timer, skift alle 6 måneder/ 1000 timer

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 10 timer

BOBCAT GRAVEMASKINER 442 (2002-2009)



SVINGDREVSGEARKASSE		
ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Labora Grease	PRODUKTANBEFALING 2 Q5 MP Calcep Grease EP 2	PRODUKTANBEFALING 3 MP Lithep Grease EP 2

Skift alle 50 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.