

BOBCAT TELESKOPLÆSSER T3093S

PERKINS 1004.40T (2000-2004)



MOTOR Perkins 1004.40T
Kapacitet: 6,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Kontroller alle 10 timer, skift alle 600 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Skift alle 100 timer

DIFFERENTIALE BAG
Kapacitet: 10 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Agrifluid HT-Plus

Kontroller alle 100 timer, skift alle 600 timer

DIFFERENTIALE FOR
Kapacitet: 10,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Agrifluid HT-Plus

Kontroller alle 100 timer, skift alle 600 timer

NAVREDUKTIONER BAG
Kapacitet: 0,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Agrifluid HT-Plus

Kontroller alle 100 timer, skift alle 600 timer

BOBCAT TELESKOPLÆSSER T3093S

PERKINS 1004.40T (2000-2004)



NAVREDUKTIONER FOR

Kapacitet: 0,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Kroontrak CVT 10W-40

PRODUKTANBEFALING 2

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 3

Agrifluid HT-Plus

Kontroller alle 100 timer, skift alle 600 timer

REDUKTIONSGEARKASSE

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Kroontrak CVT 10W-40

PRODUKTANBEFALING 2

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 3

Agrifluid HT-Plus

HYDRAULISK SYSTEM

Kapacitet: 70 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus Biosynth 46

PRODUKTANBEFALING 2

Perlus H 46

Kontroller alle 100 timer, skift alle 600 timer

HYDRAULISK BREMSESYSTEM

Kapacitet: 0,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

LHM +

Kontroller alle 100 timer, skift alle 600 timer

KØLESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.