

BOMAG TANDEMVIBRATOROTROMLER BW-AD/SL BW-80AD-2 KUBOTA D722B (1995-2011)



MOTOR Kubota D722
Kapacitet: 3,9 liter

ANVEND	KLIMA
Normalt, svovlniveau i brændstof <0,5 %	Tropisk

PRODUKTANBEFALING 1		
Multifleet SCD 30		

Kontroller alle 10 timer, skift alle 250 timer/ 12 måneder

ANVEND	KLIMA
Normalt, svovlniveau i brændstof <0,5 %	Middelhavsagtigt

PRODUKTANBEFALING 1		
Multifleet SCD 20W-20		

Kontroller alle 10 timer, skift alle 250 timer/ 12 måneder

ANVEND	KLIMA
Normalt, svovlniveau i brændstof <0,5 %	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40

Kontroller alle 10 timer, skift alle 250 timer/ 12 måneder

ANVEND	KLIMA
Normalt, svovlniveau i brændstof <0,5 %	Arktisk

PRODUKTANBEFALING 1		
Multifleet SCD 10W		

Kontroller alle 10 timer, skift alle 250 timer/ 12 måneder

ANVEND	KLIMA
Første Service	Tropisk

PRODUKTANBEFALING 1		
Multifleet SCD 30		

Skift alle 50 timer

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1		
Multifleet SCD 20W-20		

Skift alle 50 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40

Skift alle 50 timer

BOMAG TANDEMVIBRATOR TROMLER BW-AD/SL BW-80AD-2 KUBOTA D722B (1995-2011)



ANVEND		KLIMA
Første Service		Arktisk
PRODUKTANBEFALING 1		
Multifleet SCD 10W		
<i>Skift alle 50 timer</i>		

HYDRAULISK SYSTEM		
Kapacitet: 9 liter		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 32	Perlus AF 32	
<i>Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder</i>		

KØLESYSTEM		
Kapacitet: 1,9 liter		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
<i>Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder</i>		

LEDKOBLING		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.