

CASE GRAVEMASKINER MED HJUL WX

WX185 SERIE 2 (2008-2018)



MOTOR Case 667TA/MEB
Kapacitet: 16 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3

Multifleet SHPD 15W-40

DIFFERENTIALE BAG
Kapacitet: 12 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

DIFFERENTIALE FOR
Kapacitet: 11,5 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

GEAR
Kapacitet: 2,4 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

KØREREDUKTIONSENHED BAG
Kapacitet: 1 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

KØREREDUKTIONSENHED FORAN
Kapacitet: 1,5 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

HYDRAULISK SYSTEM
Kapacitet: 140 liter (Hydrauliktank), Kapacitet: 260 liter (System)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Perlus H 68

SMØREPUNKTER/NIPLER

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

CASE GRAVEMASKINER MED HJUL WX WX185 SERIE 2 (2008-2018)



KØLESYSTEM

Kapacitet: 30 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

SVINGREDUKTIONSENHED

Kapacitet: 3,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.