

CASE GUMMIHJULSLÆSSERE 21B (1995-1999)



MOTOR Perkins 504-2
Kapacitet: 5,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 2
Multifleet SHPD 15W-40

Skift alle 250 timer

DIFFERENTIALE BAG
Kapacitet: 12 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-5 85W-140

PRODUKTANBEFALING 2
Unigear LS GL-3/GL-5 85W-140

Skift alle 1000 timer

DIFFERENTIALE FOR
Kapacitet: 10 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-5 85W-140

PRODUKTANBEFALING 2
Unigear LS GL-3/GL-5 85W-140

Skift alle 1000 timer

HYDRAULISK SYSTEM
Kapacitet: 40 liter (Hydrauliktank), Kapacitet: 52 liter (Total)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2
Agrifluid HT-Plus

PRODUKTANBEFALING 3
Agrifluid HT

Skift alle 2000 timer

HYDRAULISK BREMSESYSTEM
Kapacitet: 0,2 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2
Drauliquid-S DOT 4

Skift alle 24 måneder

CASE GUMMIHJULSLÆSSERE 21B (1995-1999)



KØLESYSTEM

Kapacitet: 12 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Skift alle 2000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.