

CASE GUMMIHJULSLÆSSERE 321B

PERKINS 1004.4 (1995-2001)



MOTOR Perkins 1004.4
Kapacitet: 9,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 2
Multifleet SHPD 15W-40

Skift alle 250 timer

DIFFERENTIALE BAG
Kapacitet: 3,85 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Unigear LS GL-3/GL-5 85W-140

Skift alle 1000 timer

DIFFERENTIALE FOR
Kapacitet: 3,85 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Unigear LS GL-3/GL-5 85W-140

Skift alle 1000 timer

DIFFERENTIALE FOR OG BAG
Kapacitet: 16 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Unigear LS GL-3/GL-5 85W-140

Skift alle 1000 timer

GEAR Powershift
Kapacitet: 17,6 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Kroontrak MTH 10W-30

PRODUKTANBEFALING 2
Synfleet SHPD 10W-40

PRODUKTANBEFALING 3
Multifleet SHPD 10W-40

Skift alle 500 timer

CASE GUMMIHJULSLÆSSERE 321B PERKINS 1004.4 (1995-2001)



NAVREDUKTIONER

Kapacitet: 2,2 liter (hvert nav)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Unigear LS GL-3/GL-5 85W-140

Skift alle 1000 timer

HYDRAULISK SYSTEM

Kapacitet: 65 liter (Hydrauliktank), Kapacitet: 80 liter (Total)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Agrifluid HT

Skift alle 2000 timer

HYDRAULISK BREMSESYSTEM

Kapacitet: 1,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Skift alle 24 måneder

KØLESYSTEM

Kapacitet: 24 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Skift alle 2000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.