

# CASE GUMMIHJULSLÆSSERE 621C CASE 6T-590 (1998-2003)



**MOTOR** Case 6T-590  
Kapacitet: 15,1 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Agridiesel CRD+ 15W-40**

PRODUKTANBEFALING 2

**Dieselfleet CD+ 15W-40**

PRODUKTANBEFALING 3

**Multifleet SHPD 15W-40**

*Kontroller alle 10 timer, skift alle 250 timer*

**DIFFERENTIALE BAG**  
Kapacitet: 8,5 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Agrifluid HT-Plus**

PRODUKTANBEFALING 2

**Agrifluid HT**

*Skift alle 1000 timer*

ANVEND  
Krævende

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Agrifluid HT-Plus**

PRODUKTANBEFALING 2

**Agrifluid HT**

*Skift alle 500 timer*

ANVEND  
Første skift kun

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Agrifluid HT-Plus**

PRODUKTANBEFALING 2

**Agrifluid HT**

*Skift alle 100 timer*

# CASE GUMMIHJULSLÆSSERE 621C CASE 6T-590 (1998-2003)



## DIFFERENTIALE FOR

Kapacitet: 8,5 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1      | PRODUKTANBEFALING 2 |  |
|--------------------------|---------------------|--|
| <b>Agrifluid HT-Plus</b> | <b>Agrifluid HT</b> |  |

Skift alle 1000 timer

| ANVEND   | KLIMA   |
|----------|---------|
| Krævende | Moderat |

| PRODUKTANBEFALING 1      | PRODUKTANBEFALING 2 |  |
|--------------------------|---------------------|--|
| <b>Agrifluid HT-Plus</b> | <b>Agrifluid HT</b> |  |

Skift alle 500 timer

| ANVEND           | KLIMA   |
|------------------|---------|
| Første skift kun | Moderat |

| PRODUKTANBEFALING 1      | PRODUKTANBEFALING 2 |  |
|--------------------------|---------------------|--|
| <b>Agrifluid HT-Plus</b> | <b>Agrifluid HT</b> |  |

Skift alle 100 timer

## GEAR POWERSHIFT ZF 4/3

Kapacitet: 7,6 liter (Olieskiftskapacitet), Kapacitet: 18,9 liter (Tør efterfyld)

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2 |  |
|----------------------|---------------------|--|
| <b>SP Matic 2032</b> | <b>ATF Almirol</b>  |  |

Kontroller alle 50 timer, skift alle 1000 timer

| ANVEND           | KLIMA   |
|------------------|---------|
| Første skift kun | Moderat |

| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2 |  |
|----------------------|---------------------|--|
| <b>SP Matic 2032</b> | <b>ATF Almirol</b>  |  |

Kontroller alle 50 timer, skift alle 100 timer

# CASE GUMMIHJULSLÆSSERE 621C CASE 6T-590 (1998-2003)



## NAVREDUKTIONER

Kapacitet: 5,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Agrifluid HT-Plus**

PRODUKTANBEFALING 2

**Agrifluid HT***Skift alle 1000 timer*

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

**Agrifluid HT-Plus**

PRODUKTANBEFALING 2

**Agrifluid HT***Skift alle 500 timer*

ANVEND

Første skift kun

KLIMA

Moderat

PRODUKTANBEFALING 1

**Agrifluid HT-Plus**

PRODUKTANBEFALING 2

**Agrifluid HT***Skift alle 100 timer*

## HYDRAULISK SYSTEM

Kapacitet: 90 liter (Hydrauliktank), Kapacitet: 153 liter (Total)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**SP Matic 2032**

PRODUKTANBEFALING 2

**ATF Almirol***Kontroller alle 50 timer, skift alle 2000 timer*

## KØLESYSTEM

Kapacitet: 28 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Coolant -38 Organic NF**

PRODUKTANBEFALING 2

**Coolant -26***Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.