

CASE GUMMIHJULSLÆSSERE 621D CASE 668TA/M2 (2003-2007)



MOTOR Case 668TA/M2
Kapacitet: 16,1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 10W-40	

Skift alle 500 timer

DIFFERENTIALE BAG ZF
Kapacitet: 20,9 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agrifluid HT-Plus	Agrifluid HT	

Skift alle 1000 timer

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agrifluid HT-Plus	Agrifluid HT	

Skift alle 500 timer

DIFFERENTIALE FOR ZF
Kapacitet: 20,9 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agrifluid HT-Plus	Agrifluid HT	

Skift alle 1000 timer

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agrifluid HT-Plus	Agrifluid HT	

Skift alle 500 timer

CASE GUMMIHJULSLÆSSERE 621D CASE 668TA/M2 (2003-2007)



GEAR POWERSHIFT ZF 4/3

Kapacitet: 18,9 liter (Olieskiftskapacitet), Kapacitet: 26 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

Skift alle 1000 timer

NAVREDUKTIONER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

Agrifluid HT

Skift alle 1000 timer

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

Agrifluid HT

Skift alle 500 timer

HYDRAULISK SYSTEM

Kapacitet: 68,5 liter (Hydrauliktank), Kapacitet: 113,6 liter (Total)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

Skift alle 2000 timer

KØLESYSTEM

Kapacitet: 34,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.