

CASE GUMMIHJULSLÆSSERE 621F FPT FAHFE613Z TIER 4I/STAGE IIIB (2011-2016)



MOTOR FPT F4HFE613Z

Kapacitet: 13,25 liter (Olieskiftskapacitet), Kapacitet: 15,1 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40

Kontroller alle 10 timer, skift alle 500 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40

Skift alle 100 timer

DIFFERENTIALE BAG ZF MT-L3065-II

Kapacitet: 22 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

DIFFERENTIALE FOR ZF MT-L3075-II

Kapacitet: 22 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

GEAR POWERSHIFT ZF 4WG130 4/3

Kapacitet: 27 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Agrifluid HT

Kontroller alle 50 timer, skift alle 1000 timer

ANVEND	KLIMA
Krævende (alternativ)	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Agrifluid HT

Kontroller alle 50 timer, skift alle 500 timer

CASE GUMMIHJULSLÆSSERE 621F FPT FAHFE613Z TIER 4I/STAGE IIIB (2011-2016)



HYDRAULISK SYSTEM

Kapacitet: 148 liter (System), Kapacitet: 91 liter (Tank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus Biosynth 46

PRODUKTANBEFALING 2

Perlus H 46

Kontroller alle 50 timer, skift alle 2000 timer

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

KØLESYSTEM

Kapacitet: 28,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 50 timer, skift alle 2000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.