

CASE GUMMIHJULSLÆSSERE 721B XT

CASE 6T-830 (1994-1999)



MOTOR Case 6T-830
Kapacitet: 20,8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	

Kontroller alle 10 timer, skift alle 250 timer

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Asyntho 5W-30	Armado Synth 5W-30

Kontroller alle 10 timer, skift alle 250 timer

DIFFERENTIALE BAG

Kapacitet: 8,5 liter, Kapacitet: 1 liter (LS-additiv)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Unigear LS GL-3/GL-5 85W-140		

Skift alle 1000 timer

ANVEND	KLIMA
Første skift kun	Moderat

PRODUKTANBEFALING 1		
Unigear LS GL-3/GL-5 85W-140		

Skift alle 100 timer

DIFFERENTIALE FOR

Kapacitet: 13,7 liter, Kapacitet: 1,4 liter (LS-additiv)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Unigear LS GL-3/GL-5 85W-140		

Skift alle 1000 timer

ANVEND	KLIMA
Første skift kun	Moderat

PRODUKTANBEFALING 1		
Unigear LS GL-3/GL-5 85W-140		

Skift alle 100 timer

CASE GUMMIHJULSLÆSSERE 721B XT CASE 6T-830 (1994-1999)



GEAR POWERSHIFT ZF 4WG180 4/3

Kapacitet: 12,3 liter (Olieskiftskapacitet), Kapacitet: 22,7 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Skift alle 1000 timer

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1	
ATF Dexron II-D	

Skift alle 1000 timer

NAVREDUKTIONER

Kapacitet: 5,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	
Unigear LS GL-3/GL-5 85W-140	

Skift alle 1000 timer

ANVEND	KLIMA
Første skift kun	Moderat

PRODUKTANBEFALING 1	
Unigear LS GL-3/GL-5 85W-140	

Skift alle 100 timer

HYDRAULISK SYSTEM

Kapacitet: 90 liter (Hydrauliktank), Kapacitet: 153 liter (Total)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Agrifluid HT

Kontroller alle 50 timer, skift alle 2000 timer

CASE GUMMIHJULSLÆSSERE 721B XT CASE 6T-830 (1994-1999)



KØLESYSTEM

Kapacitet: 30 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.