

CASE GUMMIHJULSLÆSSERE 721E CASE, 4. GEN., 667TA/EED, TIER-III (2007-2011)



MOTOR Case 667TA/EED Tier 3
Kapacitet: 14,2 liter, Filterkapacitet: 1 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3

Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 500 timer

ANVEND
Første Service

KLIMA
Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3

Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 100 timer

DIFFERENTIALE BAG

Kapacitet: 23,7 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

DIFFERENTIALE FOR

Kapacitet: 30,3 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

GEAR 4F/3R Electronic 4/3

Kapacitet: 25,6 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3

Multifleet SHPD 15W-40

Kontroller alle 50 timer, skift alle 1000 timer

NAVREDUKTIONER BAG

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

NAVREDUKTIONER FOR

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

CASE GUMMIHJULSLÆSSERE 721E CASE, 4. GEN., 667TA/EED, TIER-III (2007-2011)



HYDRAULISK SYSTEM

Kapacitet: 106 liter (Hydrauliktank), Kapacitet: 176 liter (Total)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

Kontroller alle 50 timer, skift alle 2000 timer

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

Skift alle 100 timer

KØLESYSTEM

Kapacitet: 36,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Kontroller alle 50 timer, skift alle 2000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.