

CASE MINI-GRAVERE CK/CX CX15

PERKINS 103.10 (2002-2004)



MOTOR Perkins 103-10
Kapacitet: 3,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	

Kontroller alle 10 timer, skift alle 250 timer

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Asyntho 5W-30	Armado Synth 5W-30

Kontroller alle 10 timer, skift alle 250 timer

HYDRAULISK SYSTEM

Kapacitet: 22 liter (Hydrauliktank), Kapacitet: 31 liter (Total)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	

Kontroller alle 10 timer, skift alle 2000 timer

ANVEND	KLIMA
Biologisk nedbrydelig olie	Moderat

PRODUKTANBEFALING 1		
Perlus Biosynth 46		

Kontroller alle 10 timer, skift alle 2000 timer

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
MoS2 Grease EP 2		

Skift alle 50 timer

CASE MINI-GRAVERE CK/CX CX15

PERKINS 103.10 (2002-2004)



KØLESYSTEM

Kapacitet: 4,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26*Kontroller alle 10 timer, skift alle 1000 timer*

GEARREDUKTIONSENHED

Kapacitet: 0,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90*Kontroller alle 250 timer, skift alle 2000 timer*

SVINGRING TANDHJUL

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2*Skift alle 250 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.