

CASE MINI-GRAVERE CK/CX CX18B SERIE 2 MITSUBISHI L3E (2008-2017)



MOTOR Mitsubishi L3E
Kapacitet: 3,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agridiesel MSP 15W-40

PRODUKTANBEFALING 2
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 3
Dieselfleet CD+ 15W-40

Kontroller alle 10 timer, skift alle 250 timer/ 12 måneder

HYDRAULISK SYSTEM

Kapacitet: 9 liter (Hydrauliktank), Kapacitet: 24 liter (System)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Perlus Biosynth 46

PRODUKTANBEFALING 2
Perlus H 46

Kontroller alle 250 timer, skift alle 2000 timer

SMØREPUNKTER/NIPLER

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Q7 MP Calcep Grease WR 2

PRODUKTANBEFALING 2
Caliplex HD Grease EP 2

PRODUKTANBEFALING 3
Q5 MP Calcep Grease EP 2

Skift alle 10 timer

KØLESYSTEM

Kapacitet: 3,7 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Coolant SP 15+

PRODUKTANBEFALING 2
Coolant SP 12

Kontroller alle 10 timer, skift alle 1000 timer/ 24 måneder

KØREREDUKTIONSENHED

Kapacitet: 0,33 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-5 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

CASE MINI-GRAVERE CK/CX CX18B SERIE 2 MITSUBISHI L3E (2008-2017)



SPORRULLER + MELLEMHJUL

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

SVINGRING TANDHJUL

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Q7 MP Calcep Grease WR 2	Caliplex HD Grease EP 2	Q5 MP Calcep Grease EP 2

Skift alle 50 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.