

CASE MINI-GRAVERE CK/CX CX31

PERKINS 103.15 (2002-2004)



MOTOR Perkins 103-15
Kapacitet: 5,7 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2
Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 250 timer

ANVEND
Normal

KLIMA
Koldt

PRODUKTANBEFALING 1
Kroontrak MTH 10W-30

PRODUKTANBEFALING 2
Asyntho 5W-30

PRODUKTANBEFALING 3
Armado Synth 5W-30

Kontroller alle 10 timer, skift alle 250 timer

HYDRAULISK SYSTEM

Kapacitet: 46 liter (Hydrauliktank), Kapacitet: 62 liter (Total)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2
Agrifluid HT-Plus

Kontroller alle 10 timer, skift alle 2000 timer

ANVEND
Biologisk nedbrydelig olie

KLIMA
Moderat

PRODUKTANBEFALING 1
Perlus Biosynth 46

Kontroller alle 10 timer, skift alle 2000 timer

SMØREPUNKTER/NIPLER

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
MoS2 Grease EP 2

Skift alle 50 timer

CASE MINI-GRAVERE CK/CX CX31

PERKINS 103.15 (2002-2004)

**KØLESYSTEM**

Kapacitet: 5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26*Kontroller alle 10 timer, skift alle 1000 timer***GEARREDUKTIONSENHED**

Kapacitet: 1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90*Kontroller alle 250 timer, skift alle 2000 timer***SVINGRING TANDHJUL**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2*Skift alle 250 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.