

CASE RENDEGRAVER 590 TURBO



MOTOR

Kapacitet: 11 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agridiesel MSP 15W-40

PRODUKTANBEFALING 2

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 3

Dieselfleet CD+ 15W-40

Kontroller alle 10 timer, skift alle 250 timer

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

Synfleet SHPD 10W-40

PRODUKTANBEFALING 2

Multifleet SHPD 10W-40

Kontroller alle 10 timer, skift alle 250 timer

TRANSAKSEL

Kapacitet: 45 liter (Olieskiftskapacitet), Kapacitet: 54 liter (Total)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Agrifluid HT

Kontroller alle 250 timer, skift alle 1000 timer

HYDRAULISK SYSTEM

Kapacitet: 79,5 liter (Hydrauliktank), Kapacitet: 128,7 liter (Total)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT-Plus

Kontroller alle 50 timer, skift alle 1000 timer

ANVEND

Biologisk nedbrydelig olie

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus Biosynth 46

Kontroller alle 50 timer, skift alle 1000 timer

CASE RENDEGRAVER 590 TURBO



SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Skift alle 10 timer

KØLESYSTEM

Kapacitet: 17,8 liter, Kapacitet: 18,5 liter (+ varmeapparat)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.