

# CATERPILLAR FIREHJULSLÆSSERE 257B

## SERIE 3 CATERPILLAR C3.4 DIT (2010-2013)



**MOTOR** C3.4 DIT  
Kapacitet: 10 liter

| ANVEND     | KLIMA            |
|------------|------------------|
| Foretrukne | Middelhavsagtigt |

| PRODUKTANBEFALING 1          | PRODUKTANBEFALING 2           |
|------------------------------|-------------------------------|
| <b>Agridiesel MSP 15W-40</b> | <b>Dieselfleet MSP 15W-40</b> |

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

| ANVEND     | KLIMA   |
|------------|---------|
| Foretrukne | Moderat |

| PRODUKTANBEFALING 1               | PRODUKTANBEFALING 2         | PRODUKTANBEFALING 3                  |
|-----------------------------------|-----------------------------|--------------------------------------|
| <b>Agrisynth LSP Ultra 10W-40</b> | <b>Agrisynth MSP 10W-40</b> | <b>Armado Synth LSP Ultra 10W-40</b> |

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2           | PRODUKTANBEFALING 3           |
|-------------------------------|-------------------------------|-------------------------------|
| <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2           |
|-----------------------------|-------------------------------|
| <b>Agrisynth LSP 10W-40</b> | <b>Multifleet SHPD 10W-40</b> |

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

| ANVEND                  | KLIMA            |
|-------------------------|------------------|
| Alternativ (acceptabel) | Middelhavsagtigt |

| PRODUKTANBEFALING 1           |  |
|-------------------------------|--|
| <b>Dieselfleet MSP 15W-40</b> |  |

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

| ANVEND                  | KLIMA   |
|-------------------------|---------|
| Alternativ (acceptabel) | Moderat |

| PRODUKTANBEFALING 1               | PRODUKTANBEFALING 2         | PRODUKTANBEFALING 3          |
|-----------------------------------|-----------------------------|------------------------------|
| <b>Agrisynth LSP Ultra 10W-40</b> | <b>Agrisynth MSP 10W-40</b> | <b>Agridiesel MSP 15W-40</b> |

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

# CATERPILLAR FIREHJULSLÆSSERE 257B

## SERIE 3 CATERPILLAR C3.4 DIT (2010-2013)



### HYDRAULISK SYSTEM

Kapacitet: 35 liter (Hydrauliktank), Kapacitet: 55 liter (System)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Agridiesel CRD+ 15W-40**

PRODUKTANBEFALING 2

**Dieselfleet CD+ 15W-40**

PRODUKTANBEFALING 3

**Multifleet SHPD 15W-40**

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

### KØLESYSTEM

Kapacitet: 12,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Coolant SP 17**

Kontroller alle 10 timer, skift alle 72 måneder/ 12000 timer

### KØREREDUKTIONSENHED

Kapacitet: 1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Gearlube Racing 75W-140**

Skift alle 500 timer/ 3 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.