

CATERPILLAR FIREHJULSLÆSSERE 297C

CATERPILLAR C3.4 DIT (2007-2011)



MOTOR C3.4 DIT
Kapacitet: 10 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agrisynth LSP 10W-40	Multifleet SHPD 10W-40	

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

SLUTDREV
Kapacitet: 1 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Kontroller alle 250 timer, skift alle 500 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube Racing 75W-140	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Kontroller alle 250 timer, skift alle 500 timer

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Skift alle 250 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube Racing 75W-140	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Skift alle 250 timer

CATERPILLAR FIREHJULSLÆSSERE 297C

CATERPILLAR C3.4 DIT (2007-2011)



HYDRAULISK SYSTEM

Kapacitet: 42 liter, Kapacitet: 57 liter (System)

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gear Oil Alcat 30

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Agrifluid HT

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

KØLESYSTEM

Kapacitet: 13,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 17

Kontroller alle 10 timer, skift alle 72 måneder/ 12000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.