

CATERPILLAR GRAVEMASKINER MED HJUL M315C BDM (2005 OG EFTER)



MOTOR 3054E ATAAC
Kapacitet: 8 liter

ANVEND	KLIMA
Forlænget interval (max)	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40

Skift alle 250 timer/ 1 måneder

ANVEND	KLIMA
Forlænget interval (max)	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP 10W-40	Agrisynth MSP 10W-40	Armado Synth 10W-40

Skift alle 250 timer/ 1 måneder

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40

Skift alle 500 timer/ 3 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP 10W-40	Agrisynth MSP 10W-40	Armado Synth 10W-40

Skift alle 500 timer/ 3 måneder

DIFFERENTIALE BAG
Kapacitet: 14-15,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

Kontroller alle 500 timer, skift alle 12 måneder/ 2000 timer

DIFFERENTIALE FOR
Kapacitet: 10,5-11,6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

Kontroller alle 500 timer, skift alle 12 måneder/ 2000 timer

CATERPILLAR GRAVEMASKINER MED HJUL M315C BDM (2005 OG EFTER)



GEAR

Kapacitet: 2,5 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gear Oil Alcat 30

Kontroller alle 500 timer, skift alle 12 måneder/ 2000 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

PRODUKTANBEFALING 3

Dieselfleet CD+ 15W-40

Kontroller alle 500 timer, skift alle 12 måneder/ 2000 timer

NAVREDUKTIONER

Kapacitet: 2,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Agrifluid HT

Kontroller alle 500 timer, skift alle 12 måneder/ 2000 timer

HYDRAULISK SYSTEM

Kapacitet: 135 liter (Hydrauliktank), Kapacitet: 255 liter (Total)

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 30

PRODUKTANBEFALING 2

Gear Oil Alcat 30

Kontroller alle 500 timer, skift alle 12 måneder/ 2000 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Kontroller alle 500 timer, skift alle 12 måneder/ 2000 timer

CATERPILLAR GRAVEMASKINER MED HJUL M315C BDM (2005 OG EFTER)



SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
MoS2 Grease EP 2		

ANVEND	KLIMA
Mindre krævende	Moderat

PRODUKTANBEFALING 1		
HT Q9 High Grade Grease		

KØLESYSTEM

Kapacitet: 32 liter

ANVEND	KLIMA
Forlænget interval (max)	Moderat

PRODUKTANBEFALING 1		
Coolant SP 17		

Kontroller alle 500 timer, skift alle 36 måneder/ 6000 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Coolant SP 17		

Kontroller alle 500 timer, skift alle 12 måneder/ 2000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.