

CATERPILLAR GRAVEMASKINER MED HJUL M322D D2W (2007 OG EFTER)



MOTOR C6.6 Acert
Kapacitet: 17 liter

ANVEND	KLIMA
Foretrukket, svovlniveau i brændstof <0,1%	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40	

Kontroller alle 10 timer, skift alle 500 timer

ANVEND	KLIMA
Foretrukket, svovlniveau i brændstof <0,1%	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	

Kontroller alle 10 timer, skift alle 500 timer

ANVEND	KLIMA
Alternativt, Svovlniveau i brændstof < 0,1 %	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agrisynth MSP 10W-40	Dieselfleet MSP 15W-40	

Kontroller alle 10 timer, skift alle 500 timer

ANVEND	KLIMA
Alternativt, Svovlniveau i brændstof < 0,1 %	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra FE 5W-30	Agridiesel MSP 15W-40	Dieselfleet LSP Ultra 10W-30

Kontroller alle 10 timer, skift alle 500 timer

ANVEND	KLIMA
Svovlniveau for brændstof >0,1 %, fleksibel (væskeanalyse)	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40	

Kontroller alle 250 timer

ANVEND	KLIMA
Svovlniveau for brændstof >0,1 %, fleksibel (væskeanalyse)	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	

Kontroller alle 250 timer

CATERPILLAR GRAVEMASKINER MED HJUL M322D D2W (2007 OG EFTER)



DIFFERENTIALE BAG

Kapacitet: 14,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Agrifluid HT

Kontroller alle 1 måneder/ 250 timer, skift alle 12 måneder/ 2000 timer

ANVEND

> 25 % vandring

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Agrifluid HT

Kontroller alle 1 måneder/ 250 timer, skift alle 12 måneder/ 1500 timer

DIFFERENTIALE FOR

Kapacitet: 11 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Agrifluid HT

Kontroller alle 1 måneder/ 250 timer, skift alle 12 måneder/ 2000 timer

ANVEND

> 25 % vandring

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Agrifluid HT

Kontroller alle 1 måneder/ 250 timer, skift alle 12 måneder/ 1500 timer

CATERPILLAR GRAVEMASKINER MED HJUL M322D D2W (2007 OG EFTER)



GEAR

Kapacitet: 2,5 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gear Oil Alcat 30

PRODUKTANBEFALING 2

Gear Oil Alcat 50

Kontroller alle 1 måneder/ 250 timer, skift alle 12 måneder/ 2000 timer

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

Gear Oil Alcat 10W

Kontroller alle 1 måneder/ 250 timer, skift alle 12 måneder/ 2000 timer

ANVEND

> 25 % vandring

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gear Oil Alcat 30

PRODUKTANBEFALING 2

Gear Oil Alcat 50

Kontroller alle 1 måneder/ 250 timer, skift alle 12 måneder/ 1500 timer

ANVEND

> 25 % vandring

KLIMA

Koldt

PRODUKTANBEFALING 1

Gear Oil Alcat 10W

Kontroller alle 1 måneder/ 250 timer, skift alle 12 måneder/ 1500 timer

NAVREDUKTIONER BAG

Kapacitet: 2,5 liter (hvert)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Agrifluid HT

Kontroller alle 1 måneder/ 250 timer, skift alle 12 måneder/ 2000 timer

ANVEND

> 25 % vandring

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Agrifluid HT

Kontroller alle 1 måneder/ 250 timer, skift alle 12 måneder/ 1500 timer

CATERPILLAR GRAVEMASKINER MED HJUL M322D D2W (2007 OG EFTER)



NAVREDUKTIONER FOR

Kapacitet: 2,5 liter (hvert)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Agrifluid HT

Kontroller alle 1 måneder/ 250 timer, skift alle 12 måneder/ 2000 timer

ANVEND

> 25 % vandring

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Agrifluid HT

Kontroller alle 1 måneder/ 250 timer, skift alle 12 måneder/ 1500 timer

HYDRAULISK SYSTEM

Kapacitet: 225 liter (Hydrauliktank), Kapacitet: 350 liter (System)

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gear Oil Alcat 30

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

ANVEND

Biologisk nedbrydelig olie

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus Biosynth 46

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

CATERPILLAR GRAVEMASKINER MED HJUL M322D D2W (2007 OG EFTER)



SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

ANVEND

Alternativ (acceptabel)

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 37 liter

ANVEND

Foretrukket, udvidet

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 17

Kontroller alle 10 timer, skift alle 72 måneder/ 12000 timer

ANVEND

Alternativ (acceptabel)

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 10 timer, skift alle 36 måneder/ 3000 timer

DREJEGEAR

Kapacitet: 9 kg

ANVEND

Alternativ (acceptabel)

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.