

CATERPILLAR GRAVEMASKINER MED LARVEBÅND 225D 6RG (1989-1992)



MOTOR

Kapacitet: 19 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3

Multifleet SHPD 15W-40

Skift alle 250 timer/ 1 måneder

SLUTDREV

Kapacitet: 11,3 liter (hver side)

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gear Oil Alcat 50

Kontroller alle 1 måneder/ 250 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 30

Kontroller alle 1 måneder/ 250 timer

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

Gear Oil Alcat 10W

Kontroller alle 1 måneder/ 250 timer

HYDRAULISK SYSTEM

Kapacitet: 303 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 10W

Kontroller alle 3 måneder/ 500 timer, skift alle 12 måneder/ 2000 timer

CATERPILLAR GRAVEMASKINER MED LARVEBÅND 225D 6RG (1989-1992)



SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

KØLESYSTEM

Kapacitet: 27 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 17

Skift alle 2000 timer/ 12 måneder

SVINGREDUKTIONSENHED

Kapacitet: 28 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gear Oil Alcat 50

Kontroller alle 1 måneder/ 250 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 30

Kontroller alle 1 måneder/ 250 timer

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

Gear Oil Alcat 10W

Kontroller alle 1 måneder/ 250 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.