

CATERPILLAR GRAVEMASKINER MED LARVEBÅND 316E L YZZ (2011 OG EFTER)



MOTOR C4.4 Acert
Kapacitet: 16 liter

ANVEND	KLIMA
Foretrukne	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40	

Kontroller alle 10 timer, skift alle 3 måneder/ 500 timer

ANVEND	KLIMA
Foretrukne	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	

Kontroller alle 10 timer, skift alle 3 måneder/ 500 timer

ANVEND	KLIMA
Alternativ (acceptabel)	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agrisynth MSP 10W-40	Dieselfleet MSP 15W-40	

Kontroller alle 10 timer, skift alle 3 måneder/ 500 timer

ANVEND	KLIMA
Alternativ (acceptabel)	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra FE 5W-30	Agridiesel MSP 15W-40	Dieselfleet LSP Ultra 10W-30

Kontroller alle 10 timer, skift alle 3 måneder/ 500 timer

HYDRAULISK SYSTEM

Kapacitet: 190 liter (Olieskiftskapacitet)

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
Gear Oil Alcat 30		

Kontroller alle 10 timer, skift alle 18 måneder/ 3000 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Kontroller alle 10 timer, skift alle 18 måneder/ 3000 timer

CATERPILLAR GRAVEMASKINER MED LARVEBÅND 316E L YZZ (2011 OG EFTER)



ANVEND		KLIMA
Delvis hammer brug (50%)		Middelhavsagtigt
PRODUKTANBEFALING 1		
Gear Oil Alcat 30		

Kontroller alle 10 timer, skift alle 1000 timer

ANVEND		KLIMA
Delvis hammer brug (50%)		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Kontroller alle 10 timer, skift alle 1000 timer

ANVEND		KLIMA
Fuldtids habberbrug (100 %)		Middelhavsagtigt
PRODUKTANBEFALING 1		
Gear Oil Alcat 30		

Kontroller alle 10 timer, skift alle 600 timer

ANVEND		KLIMA
Fuldtids habberbrug (100 %)		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Kontroller alle 10 timer, skift alle 600 timer

KØLESYSTEM		
Kapacitet: 30 liter		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Coolant SP 17		

Kontroller alle 10 timer, skift alle 36 måneder/ 6000 timer

DREJEGEAR		
Kapacitet: 18 liter		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 2000 timer/ 12 måneder



CATERPILLAR GRAVEMASKINER MED LARVEBÅND 316E L YZZ (2011 OG EFTER)


KØREREDUKTIONSENHED

Kapacitet: 5 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Kontroller alle 1 måneder/ 250 timer, skift alle 12 måneder/ 2000 timer

ANVEND		KLIMA
Normal		Arktisk
PRODUKTANBEFALING 1		
Gear Oil Alcat 10W		

Kontroller alle 1 måneder/ 250 timer, skift alle 12 måneder/ 2000 timer

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Skift alle 250 timer/ 6 måneder

ANVEND		KLIMA
Første Service		Arktisk
PRODUKTANBEFALING 1		
Gear Oil Alcat 10W		

Skift alle 250 timer/ 6 måneder

CATERPILLAR GRAVEMASKINER MED LARVEBÅND 316E L YZZ (2011 OG EFTER)


SVINGREDUKTIONSENHED

Kapacitet: 2,4 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

ANVEND		KLIMA
Normal		Arktisk
PRODUKTANBEFALING 1		
Gear Oil Alcat 10W		

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Skift alle 250 timer/ 6 måneder

ANVEND		KLIMA
Første Service		Arktisk
PRODUKTANBEFALING 1		
Gear Oil Alcat 10W		

Skift alle 250 timer/ 6 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.