

CATERPILLAR GRAVEMASKINER MED LARVEBÅND 345D (2009 OG EFTER)



MOTOR C13 Acert
Kapacitet: 42 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 3 måneder/ 500 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Synfleet SHPD 10W-40	Multifleet SHPD 10W-40	

Kontroller alle 10 timer, skift alle 3 måneder/ 500 timer

HYDRAULISK SYSTEM
Kapacitet: 262 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
Gear Oil Alcat 30		

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak CVT 10W-40	Agridiesel CRD+ 15W-40	Agrifluid Synth XHP Ultra

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

ANVEND	KLIMA
Vedvarende anvendelse af hammer	Middelhavsagtigt

PRODUKTANBEFALING 1		
Gear Oil Alcat 30		

Kontroller alle 10 timer, skift alle 600 timer

ANVEND	KLIMA
Vedvarende anvendelse af hammer	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak CVT 10W-40	Agridiesel CRD+ 15W-40	Agrifluid Synth XHP Ultra

Kontroller alle 10 timer, skift alle 600 timer

CATERPILLAR GRAVEMASKINER MED LARVEBÅND 345D (2009 OG EFTER)



ANVEND		KLIMA
Delvis hammer brug (50%)		Middelhavsagtigt
PRODUKTANBEFALING 1		
Gear Oil Alcat 30		

Kontroller alle 10 timer, skift alle 1000 timer

ANVEND		KLIMA
Delvis hammer brug (50%)		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak CVT 10W-40	Agridiesel CRD+ 15W-40	Agrifluid Synth XHP Ultra

Kontroller alle 10 timer, skift alle 1000 timer

KØLESYSTEM		
Kapacitet: 75,5 liter, Kapacitet: 4,5 liter (Tank)		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Coolant SP 17		

Kontroller alle 10 timer, skift alle 72 måneder/ 12000 timer

DREJEGEAR		
Kapacitet: 35 liter		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 2000 timer/ 12 måneder



CATERPILLAR GRAVEMASKINER MED LARVEBÅND 345D (2009 OG EFTER)



KØREREDUKTIONSENHED

Kapacitet: 15 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Kontroller alle 1 måneder/ 250 timer, skift alle 12 måneder/ 2000 timer

ANVEND		KLIMA
Normal		Arktisk
PRODUKTANBEFALING 1		
Gear Oil Alcat 10W		

Kontroller alle 1 måneder/ 250 timer, skift alle 12 måneder/ 2000 timer

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Skift alle 250 timer

ANVEND		KLIMA
Første Service		Arktisk
PRODUKTANBEFALING 1		
Gear Oil Alcat 10W		

Skift alle 250 timer

PUMPEDREV

Kapacitet: 0,6 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40

Kontroller alle 500 timer, skift alle 5000 timer

CATERPILLAR GRAVEMASKINER MED LARVEBÅND 345D (2009 OG EFTER)


SVINGREDUKTIONSENHED

Kapacitet: 10 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

ANVEND		KLIMA
Normal		Arktisk
PRODUKTANBEFALING 1		
Gear Oil Alcat 10W		

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Skift alle 250 timer

ANVEND		KLIMA
Første Service		Arktisk
PRODUKTANBEFALING 1		
Gear Oil Alcat 10W		

Skift alle 250 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.