

CATERPILLAR GUMMIHJULSLÆSSERE

938F CATERPILLAR 3116 DIT (1994-1997)



MOTOR Caterpillar 3116 DIT
Kapacitet: 20 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2
Synfleet SHPD 10W-40

PRODUKTANBEFALING 3
Dieselfleet CD+ 15W-40

Skift alle 250 timer

DIFFERENTIALE FOR + BAG

Kapacitet: 27 liter (Bag), Kapacitet: 24 liter (For)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gear Oil Alcat 30

PRODUKTANBEFALING 2
Gear Oil Alcat 50

Kontroller alle 500 timer, skift alle 2000 timer

ANVEND
Normal

KLIMA
Arktisk

PRODUKTANBEFALING 1
Gear Oil Alcat 10W

Kontroller alle 500 timer, skift alle 2000 timer

GEAR Powershift
Kapacitet: 30 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Gear Oil Alcat 30

PRODUKTANBEFALING 2
Gear Oil Alcat 50

Kontroller alle 500 timer, skift alle 1000 timer

ANVEND
Normal

KLIMA
Koldt

PRODUKTANBEFALING 1
Gear Oil Alcat 10W

Kontroller alle 500 timer, skift alle 1000 timer

CATERPILLAR GUMMIHJULSLÆSSERE

938F CATERPILLAR 3116 DIT (1994-1997)



HYDRAULISK SYSTEM

Kapacitet: 90 liter (Hydrauliksystem inkl. tank), Kapacitet: 55 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Synfleet SHPD 10W-40

Kontroller alle 500 timer, skift alle 2000 timer

HYDRAULISK BREMSESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 10W

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.