

CATERPILLAR GUMMIHJULSLÆSSERE

950G CATERPILLAR 3126 DITA (1998-2001)



MOTOR Caterpillar 3126 DITA
Kapacitet: 34 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

PRODUKTANBEFALING 3

Dieselfleet CD+ 15W-40

Skift alle 250 timer

DIFFERENTIALE BAG

Kapacitet: 0,5 liter (LS-additiv), Kapacitet: 36,5 liter (Total)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

DIFFERENTIALE FOR

Kapacitet: 0,5 liter (LS-additiv), Kapacitet: 36,5 liter (Total)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

GEAR Powershift
Kapacitet: 34 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1

Gear Oil Alcat 30

PRODUKTANBEFALING 2

Gear Oil Alcat 50

Kontroller alle 500 timer, skift alle 1000 timer

ANVEND
Normal

KLIMA
Koldt

PRODUKTANBEFALING 1

Gear Oil Alcat 10W

Kontroller alle 500 timer, skift alle 1000 timer

CATERPILLAR GUMMIHJULSLÆSSERE

950G CATERPILLAR 3126 DITA (1998-2001)



HYDRAULISK SYSTEM

Kapacitet: 88 liter (Hydrauliktank)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Kontroller alle 500 timer, skift alle 2000 timer

ANVEND		KLIMA
Biologisk nedbrydelig olie		Moderat
PRODUKTANBEFALING 1		
Perlus Biosynth 46		

Kontroller alle 500 timer, skift alle 2000 timer

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
MoS2 Grease EP 2		

ANVEND		KLIMA
Mindre krævende		Moderat
PRODUKTANBEFALING 1		
HT Q9 High Grade Grease		

KØLESYSTEM

Kapacitet: 55 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Coolant SP 17		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.