

CATERPILLAR LÆSSEMASKINER MED LARVEBÅND 939C HYSTAT (1997 OG EFTER)



MOTOR 3046
Kapacitet: 13 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30	Asyntho 5W-30

Kontroller alle 10 timer, skift alle 100 timer

SLUTDREV
Kapacitet: 14,7 liter

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1		
Gear Oil Alcat 50		

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gear Oil Alcat 30		

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

ANVEND		KLIMA
Normal		Arktisk
PRODUKTANBEFALING 1		
Gear Oil Alcat 10W		

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

HYDRAULISK SYSTEM
Kapacitet: 56,8 liter (Hydrauliktank)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	Gear Oil Alcat 10W

Kontroller alle 10 timer, skift alle 6 måneder/ 1000 timer

ANVEND		KLIMA
Biologisk nedbrydelig olie		Moderat
PRODUKTANBEFALING 1		
Perlus Biosynth 46		

Kontroller alle 10 timer, skift alle 6 måneder/ 1000 timer

CATERPILLAR LÆSSEMASKINER MED LARVEBÅND 939C HYSTAT (1997 OG EFTER)



KØLESYSTEM

Kapacitet: 21 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 10 timer, skift alle 24 måneder/ 3000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.