

CATERPILLAR LÆSSERE, SKID-STEER

272C CATERPILLAR C3,4T (2007-2013)



MOTOR 3044C DIT

Kapacitet: 10 liter, Filterkapacitet: 1 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Kontroller alle 250 timer, skift alle 500 timer/ 12 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agrisynth LSP 10W-40	Multifleet SHPD 10W-40	

Kontroller alle 250 timer, skift alle 500 timer/ 12 måneder

HYDRAULISK SYSTEM HYDROSTATISK DREV

Kapacitet: 57 liter (Hydrauliksystem inkl. tank), Kapacitet: 42 liter (Hydrauliktank)

ANVEND	KLIMA
Foretrukne	Moderat

PRODUKTANBEFALING 1		
Gear Oil Alcat 10W		

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
Gear Oil Alcat 30		

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gear Oil Alcat 10W		

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

ANVEND	KLIMA
Alternativ (acceptabel)	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

CATERPILLAR LÆSSERE, SKID-STEER

272C CATERPILLAR C3,4T (2007-2013)



ANVEND		KLIMA
Biologisk nedbrydelig olie		Moderat
PRODUKTANBEFALING 1		
Perlus Biosynth 46		
<i>Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder</i>		

EKSTERNE SMØREPUNKTER

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

KØLESYSTEM		
Kapacitet: 13,9 liter		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Coolant SP 17		
<i>Skift alle 12000 timer/ 72 måneder</i>		

DRIVKÆDEHUS		
Kapacitet: 11 liter		
ANVEND		KLIMA
Foretrukne		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
<i>Kontroller alle 3 måneder/ 500 timer, skift alle 6 måneder/ 1000 timer</i>		

ANVEND		KLIMA
Foretrukne		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agrisynth LSP 10W-40	Multifleet SHPD 10W-40	
<i>Kontroller alle 3 måneder/ 500 timer, skift alle 6 måneder/ 1000 timer</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.