

CATERPILLAR LÆSSERE, SKID-STEER 272D XHP ETL/SHY/CATERPILLAR C3.8 (2013 OG EFTER)



MOTOR C3.8 Tier 4i
Kapacitet: 13,2 liter

ANVEND	KLIMA
Foretrukket, svovlniveau i brændstof <0,05%	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40	

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

ANVEND	KLIMA
Foretrukket, svovlniveau i brændstof <0,05%	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

ANVEND	KLIMA
Svovlniveau i brændstof 0,5 - 1%	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40	

Kontroller alle 10 timer, skift alle 6 måneder/ 250 timer

ANVEND	KLIMA
Svovlniveau i brændstof 0,5 - 1%	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40

Kontroller alle 10 timer, skift alle 6 måneder/ 250 timer

ANVEND	KLIMA
Alternativt, Svovlniveau i brændstof < 0,05 %	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40	

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

ANVEND	KLIMA
Alternativt, Svovlniveau i brændstof < 0,05 %	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

ANVEND	KLIMA
Svovlniveau i brændstof 0,05-0,5 %	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40	

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

CATERPILLAR LÆSSERE, SKID-STEER 272D XHP ETL/SHY/CATERPILLAR C3.8 (2013 OG EFTER)



ANVEND		KLIMA
Svovlniveau i brændstof 0,05-0,5 %		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40
<i>Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder</i>		

HYDRAULISK SYSTEM		
Kapacitet: 55 liter (Hydrauliksystem inkl. tank), Kapacitet: 39 liter (Hydrauliktank)		
ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1		
Gear Oil Alcat 30		
<i>Kontroller alle 10 timer, skift alle 2000 timer</i>		

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30
<i>Kontroller alle 10 timer, skift alle 2000 timer</i>		

ANVEND		KLIMA
Biologisk nedbrydelig olie		Moderat
PRODUKTANBEFALING 1		
Perlus Biosynth 46		
<i>Kontroller alle 10 timer, skift alle 2000 timer</i>		

SMØREPUNKTER/NIPLER		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
MoS2 Grease EP 2		



CATERPILLAR LÆSSERE, SKID-STEER 272D XHP ETL/SHY/CATERPILLAR C3.8 (2013 OG EFTER)

**KØLESYSTEM**

Kapacitet: 15,5 liter

ANVEND

Foretrukket, udvidet

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 17*Kontroller alle 10 timer, skift alle 72 måneder/ 12000 timer*

ANVEND

Alternativ (acceptabel)

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF*Kontroller alle 10 timer, skift alle 36 måneder/ 3000 timer***DRIVÆDEHUS**

Kapacitet: 10,2 liter (hvert)

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Agrisynth MSP 10W-40

PRODUKTANBEFALING 2

Dieselfleet MSP 15W-40*Kontroller alle 3 måneder/ 500 timer, skift alle 6 måneder/ 1000 timer*

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra FE 5W-30

PRODUKTANBEFALING 2

Agridiesel MSP 15W-40

PRODUKTANBEFALING 3

Dieselfleet LSP Ultra 10W-30*Kontroller alle 3 måneder/ 500 timer, skift alle 6 måneder/ 1000 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.