

CATERPILLAR MASKINER TIL SKOVBRUG

320D FM TIER 3 GKS (2006-2011)



MOTOR C6.4 Acert
Kapacitet: 30 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Skift alle 500 timer/ 3 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Synfleet SHPD 10W-40	Multifleet SHPD 10W-40	

Skift alle 500 timer/ 3 måneder

SLUTDREV
Kapacitet: 8 liter (hvert nav)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Kontroller alle 1 måneder/ 250 timer, skift alle 12 måneder/ 2000 timer

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1		
Gear Oil Alcat 10W		

Kontroller alle 1 måneder/ 250 timer, skift alle 12 måneder/ 2000 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Skift alle 250 timer/ 1 måneder

ANVEND	KLIMA
Første Service	Arktisk

PRODUKTANBEFALING 1		
Gear Oil Alcat 10W		

Skift alle 250 timer/ 1 måneder

HYDRAULISK SYSTEM
Kapacitet: 138 liter (Total)

CATERPILLAR MASKINER TIL SKOVBRUG

320D FM TIER 3 GKS (2006-2011)



ANVEND Normal		KLIMA Middelhavsagtigt
PRODUKTANBEFALING 1 Gear Oil Alcat 30		
Skift alle 2000 timer/ 12 måneder		
ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Kroontrak CVT 10W-40	PRODUKTANBEFALING 2 Agridiesel CRD+ 15W-40	PRODUKTANBEFALING 3 Agrifluid Synth XHP Ultra
Skift alle 2000 timer/ 12 måneder		
ANVEND 50% anvendelse af afbryder		KLIMA Middelhavsagtigt
PRODUKTANBEFALING 1 Gear Oil Alcat 30		
Skift alle 1000 timer		
ANVEND 50% anvendelse af afbryder		KLIMA Moderat
PRODUKTANBEFALING 1 Kroontrak CVT 10W-40	PRODUKTANBEFALING 2 Agridiesel CRD+ 15W-40	PRODUKTANBEFALING 3 Agrifluid Synth XHP Ultra
Skift alle 1000 timer		
ANVEND 100% anvendelse af afbryder		KLIMA Middelhavsagtigt
PRODUKTANBEFALING 1 Gear Oil Alcat 30		
Skift alle 600 timer		
ANVEND 100% anvendelse af afbryder		KLIMA Moderat
PRODUKTANBEFALING 1 Kroontrak CVT 10W-40	PRODUKTANBEFALING 2 Agridiesel CRD+ 15W-40	PRODUKTANBEFALING 3 Agrifluid Synth XHP Ultra
Skift alle 600 timer		

CATERPILLAR MASKINER TIL SKOVBRUG

320D FM TIER 3 GKS (2006-2011)



SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

ANVEND

Mindre krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

HT Q9 High Grade Grease

KØLESYSTEM

Kapacitet: 25 liter, Kapacitet: 1,5 liter (Tank)

ANVEND

Forlænget interval (max)

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 17

Skift alle 12000 timer/ 72 måneder

DREJEGEAR

Kapacitet: 22 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Kontroller alle 12 måneder/ 2000 timer

LARVEBÅNDRULLER

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

SPOR MELLEMHJUL

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 30

CATERPILLAR MASKINER TIL SKOVBRUG

320D FM TIER 3 GKS (2006-2011)

**SVINGREDUKTIONSENHED**

Kapacitet: 8 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

ANVEND		KLIMA
Normal		Arktisk
PRODUKTANBEFALING 1		
Gear Oil Alcat 10W		

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Skift alle 250 timer

ANVEND		KLIMA
Første Service		Arktisk
PRODUKTANBEFALING 1		
Gear Oil Alcat 10W		

Skift alle 250 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.