

CATERPILLAR MOTORDREVNE VEJHØVLE

120H 124 (2004-2008)



MOTOR 3126B ATAAC
Kapacitet: 29,5 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2
Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3
Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 3 måneder/ 500 timer

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrisynth LSP 10W-40

PRODUKTANBEFALING 2
Multifleet SHPD 10W-40

Kontroller alle 10 timer, skift alle 3 måneder/ 500 timer

DIFFERENTIALE

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gear Oil Alcat 30

PRODUKTANBEFALING 2
Gear Oil Alcat 50

Kontroller alle 10 timer, skift alle 6 måneder/ 1000 timer

ANVEND
Normal

KLIMA
Arktisk

PRODUKTANBEFALING 1
Gear Oil Alcat 10W

Kontroller alle 10 timer, skift alle 6 måneder/ 1000 timer

GEAR
Kapacitet: 34 liter (+ differentiale)

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Gear Oil Alcat 30

PRODUKTANBEFALING 2
Gear Oil Alcat 50

Kontroller alle 10 timer, skift alle 6 måneder/ 1000 timer

ANVEND
Normal

KLIMA
Koldt

PRODUKTANBEFALING 1
Gear Oil Alcat 10W

Kontroller alle 10 timer, skift alle 6 måneder/ 1000 timer

CATERPILLAR MOTORDREVNE VEJHØVLE

120H 124 (2004-2008)



HYDRAULISK SYSTEM

Kapacitet: 55 liter (Hydrauliktank), Kapacitet: 82 liter (System)

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1		
Gear Oil Alcat 30		

Kontroller alle 100 timer, skift alle 4000 timer

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

Kontroller alle 100 timer, skift alle 4000 timer

HJULSPINDELLEJE FOR

Kapacitet: 0,5 liter (hver side)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Kontroller alle 100 timer, skift alle 2000 timer/ 24 måneder

ANVEND		KLIMA
Normal		Arktisk
PRODUKTANBEFALING 1		
Gear Oil Alcat 10W		

Kontroller alle 100 timer, skift alle 2000 timer/ 24 måneder

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
MoS2 Grease EP 2		

Skift alle 100 timer

ANVEND		KLIMA
Mindre krævende		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
HT Q9 High Grade Grease	Labora Grease	

Skift alle 100 timer

CATERPILLAR MOTORDREVNE VEJHØVLE

120H 124 (2004-2008)

**KØLESYSTEM**

Kapacitet: 38 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 17*Kontroller alle 10 timer, skift alle 72 måneder/ 12000 timer***DRIVGEARKASSE**

Kapacitet: 7 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140*Skift alle 2000 timer/ 24 måneder*

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube Racing 75W-140

PRODUKTANBEFALING 2

SP Gear 1011

PRODUKTANBEFALING 3

Syngear TDL 75W-90*Skift alle 2000 timer/ 24 måneder***TANDEMDREV-ENHED**

Kapacitet: 61 liter (hver side)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 30

PRODUKTANBEFALING 2

Gear Oil Alcat 50*Kontroller alle 100 timer, skift alle 2000 timer/ 24 måneder*

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

Gear Oil Alcat 10W*Kontroller alle 100 timer, skift alle 2000 timer/ 24 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.