

CATERPILLAR MOTORDREVNE VEJHØVLE

12H ES 2GS (1995-1996)



MOTOR 3306 Turbo
Kapacitet: 29 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 1 måneder/ 250 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agrisynth LSP 10W-40	Multifleet SHPD 10W-40	

Kontroller alle 10 timer, skift alle 1 måneder/ 250 timer

ANVEND	KLIMA
Normal, brændstof med svovlindhold > 1,5% af vægt	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 1 måneder/ 125 timer

ANVEND	KLIMA
Normal, brændstof med svovlindhold > 1,5% af vægt	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agrisynth LSP 10W-40	Multifleet SHPD 10W-40	

Kontroller alle 10 timer, skift alle 1 måneder/ 125 timer

GEAR

Kapacitet: 47 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1		
Gear Oil Alcat 10W		

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

CATERPILLAR MOTORDREVNE VEJHØVLE

12H ES 2GS (1995-1996)



TANDEMDREV

Kapacitet: 64 liter (hver side)

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gear Oil Alcat 30

PRODUKTANBEFALING 2

Gear Oil Alcat 50

Kontroller alle 1 måneder/ 250 timer, skift alle 12 måneder/ 2000 timer

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

Gear Oil Alcat 10W

Kontroller alle 1 måneder/ 250 timer, skift alle 12 måneder/ 2000 timer

HYDRAULISK SYSTEM

Kapacitet: 38 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 30

PRODUKTANBEFALING 2

Gear Oil Alcat 30

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Asyntho 5W-30

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

HJULSPINDELLEJE FOR

Kapacitet: 0,5 liter (hvert hjul)

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gear Oil Alcat 30

PRODUKTANBEFALING 2

Gear Oil Alcat 50

Kontroller alle 3 måneder/ 500 timer

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

Gear Oil Alcat 10W

Kontroller alle 3 måneder/ 500 timer

CATERPILLAR MOTORDREVNE VEJHØVLE

12H ES 2GS (1995-1996)

**KØLESYSTEM**

Kapacitet: 45 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF*Kontroller alle 10 timer, skift alle 24 måneder/ 3000 timer***DRIVGEARKASSE**

Kapacitet: 7 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140*Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder*

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

PRODUKTANBEFALING 3

Gearlube GL-5 80W-90*Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.