

CATERPILLAR MOTORDREVNE VEJHØVLE

140G 13W (1974-1998)



MOTOR 3306
Kapacitet: 27 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Multifleet SCD 40	Multifleet SCD 30

Kontroller alle 10 timer, skift alle 1 måneder/ 250 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Kontroller alle 10 timer, skift alle 1 måneder/ 250 timer

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1		
Multifleet SCD 10W		

Kontroller alle 10 timer, skift alle 1 måneder/ 250 timer

TANDEMDREV
Kapacitet: 64 liter (hver side)

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Multifleet SCD 50	Multifleet SCD 40

Kontroller alle 1 måneder/ 250 timer, skift alle 12 måneder/ 2000 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Multifleet SCD 30		

Kontroller alle 1 måneder/ 250 timer, skift alle 12 måneder/ 2000 timer

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1		
Multifleet SCD 10W		

Kontroller alle 1 måneder/ 250 timer, skift alle 12 måneder/ 2000 timer

CATERPILLAR MOTORDREVNE VEJHØVLE

140G 13W (1974-1998)



TRANSAKSEL

Kapacitet: 83 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 40

PRODUKTANBEFALING 2

Multifleet SCD 30

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 2

Multifleet SHPD 15W-40

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

PRODUKTANBEFALING 3

Multifleet SHPD 10W-40

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

HYDRAULISK SYSTEM

Kapacitet: 76 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

HDX 30

Kontroller alle 100 timer, skift alle 12 måneder/ 2000 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

HDX 10W

Kontroller alle 100 timer, skift alle 12 måneder/ 2000 timer

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

Skift alle 50 timer

CATERPILLAR MOTORDREVNE VEJHØVLE

140G 13W (1974-1998)



KØLESYSTEM

Kapacitet: 40 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

HJULSPINDELHUS FOR

Kapacitet: 3,8 liter (hver side)

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 50

PRODUKTANBEFALING 2

Multifleet SCD 40

Kontroller alle 3 måneder/ 500 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 30

Kontroller alle 3 måneder/ 500 timer

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

Multifleet SCD 10W

Kontroller alle 3 måneder/ 500 timer

CATERPILLAR MOTORDREVNE VEJHØVLE

140G 13W (1974-1998)



RINGDREVENHED

Kapacitet: 7,6 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 50

PRODUKTANBEFALING 2

Multifleet SCD 40

Skift alle 2000 timer/ 12 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 2000 timer/ 12 måneder

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

Multifleet SCD 10W

Skift alle 2000 timer/ 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.