CATERPILLAR MOTOR GRADERS 140M B9M (2006 AND AFTER)



| ENGINE C7 Acert Capacity: 25 liter | | |
|---|---------------------------|--------------------------|
| USE | | CLIMATE |
| Preferred | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 |
| Charles averaged to be averaged as a second | 1.2 maginths / 500 having | |

Check every 10 hours, change every 3 months/ 500 hours

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Preferred | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Agrisynth LSP 10W-40 | Multifleet SHPD 10W-40 | |

Check every 10 hours, change every 3 months/ 500 hours

| USE | | CLIMATE |
|--------------------------|--------------------------|---------------|
| Alternative (acceptable) | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Agridiesel CRD+ 15W-40 | Multifleet SHPD 15W-40 | |

Check every 10 hours, change every 3 months/ 500 hours

| use Alternative (acceptable) | | climate Moderate |
|------------------------------|--------------------------|--------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Synfleet SHPD 10W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 10W-40 |

Check every 10 hours, change every 3 months/ 500 hours

| GEARBOX ALL WHEEL DRIVE Capacity: 7 liter (each side) | |
|--|---------------|
| USE | CLIMATE |
| Normal | Mediterranean |
| PRODUCT RECOMMENDATION 1 | |
| Gear Oil Alcat 50 | |
| | • |

Check every 3 months/ 500 hours, change every 24 months/ 2000 hours

TANDEM DRIVE

Capacity: 64,4 liter (each side)

We are unable to give a standard recommendation for this component. Please contact our service department.

CATERPILLAR MOTOR GRADERS 140M B9M (2006 AND AFTER)



| TRANSAXLE Capacity: 64,4 liter | | |
|--------------------------------------|--------------------------|---------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 30 | Gear Oil Alcat 50 | |
| Check every 10 hours, change every 6 | months/ 1000 hours | |
| USE | | CLIMATE |
| Normal | | Cold |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 10W | | |
| Check every 10 hours, change every 6 | months/ 1000 hours | |

| USE | | CLIMATE |
|-----------------------------------|--------------------------|--------------------------|
| Normal | | Tropical |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 | Gear Oil Alcat 30 |
| Check every 100 hours, change eve | ry 12 months/ 2000 hours | |
| SE | | CLIMATE |
| Normal | | Mediterranean |
| RODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| grifluid HT-Plus | Kroontrak MTH 10W-30 | Agrifluid HT |
| Check every 100 hours, change eve | ry 12 months/ 2000 hours | |
| SE | | CLIMATE |
| Normal | | Moderate |
| RODUCT RECOMMENDATION 1 | | |
| Sear Oil Alcat 10W | | |

CATERPILLAR MOTOR GRADERS 140M B9M (2006 AND AFTER)



| WHEEL SPINDLE BEARING FRONT Capacity: 0,9 liter (each wheel) | | | |
|---|-----------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Gear Oil Alcat 30 | Gear Oil Alcat 50 | | |
| Check every 3 months/ 500 hours, change | every 24 months/ 2000 hours | | |
| USE | | CLIMATE | |
| Normal | | Arctic | |
| PRODUCT RECOMMENDATION 1 | | | |
| Gear Oil Alcat 10W | | | |
| Check every 3 months/ 500 hours, change every 24 months/ 2000 hours | | | |

| COOLING SYSTEM Capacity: 29 liter | | |
|--------------------------------------|----------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 17 | | |
| | <u> </u> | <u> </u> |

Check every 10 hours, change every 72 months/ 12000 hours

| CIRCLE DRIVE GEARBOX Capacity: 7,2 liter | | |
|--|------------------------------|---------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 85W-140 | Unigear LS GL-3/GL-5 85W-140 | |

Check every 1 months/ 100 hours, change every 24 months/ 2000 hours

| Gearlube Racing 75W-140 | SP Gear 1011 | Syngear TDL 75W-90 |
|--------------------------|--------------------------|--------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Normal | | Moderate |
| USE | | CLIMATE |

Check every 1 months/ 100 hours, change every 24 months/ 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.