

CATERPILLAR MOTORDREVNE VEJHØVLE 140M SERIE 2 M9D/M9J/R9G/R9M (2011 OG EFTER)



MOTOR C9.3 Acert
Kapacitet: 30 liter

ANVEND	KLIMA
Foretrukne	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40

Kontroller alle 10 timer, skift alle 3 måneder/ 500 timer

ANVEND	KLIMA
Foretrukne	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Armado Synth MSP 5W-40	Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30

Kontroller alle 10 timer, skift alle 3 måneder/ 500 timer

ANVEND	KLIMA
Alternativ (acceptabel)	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Agrisynth MSP 10W-40	Dieselfleet MSP 15W-40

Kontroller alle 10 timer, skift alle 3 måneder/ 500 timer

ANVEND	KLIMA
Alternativ (acceptabel)	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra 10W-40	Agridiesel MSP 15W-40	Armado Synth LSP Ultra 10W-40

Kontroller alle 10 timer, skift alle 3 måneder/ 500 timer

GEAR Powershift
Kapacitet: 65 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Gear Oil Alcat 30	Gear Oil Alcat 50

Kontroller alle 10 timer, skift alle 6 måneder/ 1000 timer

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1
Gear Oil Alcat 10W

Kontroller alle 10 timer, skift alle 6 måneder/ 1000 timer

CATERPILLAR MOTORDREVNE VEJHØVLE 140M SERIE 2 M9D/M9J/R9G/R9M (2011 OG EFTER)



HYDRAULISK SYSTEM

Kapacitet: 100 liter

ANVEND

Normal

KLIMA

Tropisk

PRODUKTANBEFALING 1

Gear Oil Alcat 30

Kontroller alle 10 timer, skift alle 24 måneder/ 4000 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 10W

Kontroller alle 10 timer, skift alle 24 måneder/ 4000 timer

ANVEND

Biologisk nedbrydelig olie

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus Biosynth 46

Kontroller alle 10 timer, skift alle 24 måneder/ 4000 timer

HJULSPINDELLEJE FOR

Kapacitet: 0,5 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gear Oil Alcat 30

PRODUKTANBEFALING 2

Gear Oil Alcat 50

Kontroller alle 3 måneder/ 500 timer, skift alle 24 måneder/ 2000 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 10W

Kontroller alle 3 måneder/ 500 timer, skift alle 24 måneder/ 2000 timer

KØLESYSTEM

Kapacitet: 56 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 17

Kontroller alle 10 timer, skift alle 72 måneder/ 12000 timer

CATERPILLAR MOTORDREVNE VEJHØVLE 140M SERIE 2 M9D/M9J/R9G/R9M (2011 OG EFTER)



RINGDREVENHED

Kapacitet: 7 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140

Skift alle 2000 timer/ 24 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube Racing 75W-140

PRODUKTANBEFALING 2

SP Gear 1011

PRODUKTANBEFALING 3

Syngear TDL 75W-90

Skift alle 2000 timer/ 24 måneder

TANDEMDREV-ENHED

Kapacitet: 64 liter, Kapacitet: 1 liter (LS-additiv)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.