

CATERPILLAR MOTORDREVNE VEJHØVLE

160H XZK (1994-2002)



MOTOR 3176C ATAAC
Kapacitet: 35 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 3 måneder/ 500 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agrisynth LSP 10W-40	Multifleet SHPD 10W-40	

Kontroller alle 10 timer, skift alle 3 måneder/ 500 timer

TANDEMDREV
Kapacitet: 64 liter (hver side)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Kontroller alle 10 timer, skift alle 6 måneder/ 1000 timer

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1		
Gear Oil Alcat 10W		

Kontroller alle 10 timer, skift alle 6 måneder/ 1000 timer

TRANSAKSEL
Kapacitet: 47 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Kontroller alle 10 timer, skift alle 6 måneder/ 1000 timer

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1		
Gear Oil Alcat 10W		

Kontroller alle 10 timer, skift alle 6 måneder/ 1000 timer

CATERPILLAR MOTORDREVNE VEJHØVLE

160H XZK (1994-2002)



HYDRAULISK SYSTEM

Kapacitet: 56 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gear Oil Alcat 30

Kontroller alle 50 timer, skift alle 4000 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Agrifluid HT

Kontroller alle 50 timer, skift alle 4000 timer

HJULSPINDELLEJE FOR

Kapacitet: 0,5 liter (hvert hjul)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 30

PRODUKTANBEFALING 2

Gear Oil Alcat 50

Kontroller alle 100 timer, skift alle 2000 timer/ 24 måneder

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

Gear Oil Alcat 10W

Kontroller alle 100 timer, skift alle 2000 timer/ 24 måneder

KØLESYSTEM

Kapacitet: 44 liter

ANVEND

Foretrukket, udvidet

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 17

Kontroller alle 10 timer, skift alle 72 måneder/ 6000 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 10 timer, skift alle 72 måneder/ 12000 timer

CATERPILLAR MOTORDREVNE VEJHØVLE

160H XZK (1994-2002)

**DRIVEGEARKASSE**

Kapacitet: 7 liter

ANVEND

Normal

KLIMA

Middelhavssagtigt

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140*Skift alle 2000 timer/ 24 måneder*

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube Racing 75W-140

PRODUKTANBEFALING 2

SP Gear 1011

PRODUKTANBEFALING 3

Syngear TDL 75W-90*Skift alle 2000 timer/ 24 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.