

# CATERPILLAR MOTORDREVNE VEJHØVLE

## 24M B9K (2006 OG EFTER)



**MOTOR** C18 Acert MEUI  
Kapacitet: 60 liter

| ANVEND                        |                               | KLIMA                         |
|-------------------------------|-------------------------------|-------------------------------|
| Foretrukne                    |                               | Middelhavsagtigt              |
| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2           | PRODUKTANBEFALING 3           |
| <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |

Kontroller alle 10 timer, skift alle 3 måneder/ 500 timer

| ANVEND                      |                               | KLIMA   |
|-----------------------------|-------------------------------|---------|
| Foretrukne                  |                               | Moderat |
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2           |         |
| <b>Agrisynth LSP 10W-40</b> | <b>Multifleet SHPD 10W-40</b> |         |

Kontroller alle 10 timer, skift alle 3 måneder/ 500 timer

| ANVEND                        |                               | KLIMA            |
|-------------------------------|-------------------------------|------------------|
| Alternativ (acceptabel)       |                               | Middelhavsagtigt |
| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2           |                  |
| <b>Agridiesel CRD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |                  |

Kontroller alle 10 timer, skift alle 3 måneder/ 500 timer

| ANVEND                      |                               | KLIMA                         |
|-----------------------------|-------------------------------|-------------------------------|
| Alternativ (acceptabel)     |                               | Moderat                       |
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2           | PRODUKTANBEFALING 3           |
| <b>Synfleet SHPD 10W-40</b> | <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 10W-40</b> |

Kontroller alle 10 timer, skift alle 3 måneder/ 500 timer

**DIFFERENTIAL + NAVREDUKTIONER**  
Kapacitet: 184 liter

| ANVEND                   |                          | KLIMA            |
|--------------------------|--------------------------|------------------|
| Normal                   |                          | Middelhavsagtigt |
| PRODUKTANBEFALING 1      | PRODUKTANBEFALING 2      |                  |
| <b>Gear Oil Alcat 30</b> | <b>Gear Oil Alcat 50</b> |                  |

Kontroller alle 3 måneder/ 500 timer, skift alle 6 måneder/ 1000 timer

| ANVEND                    |  | KLIMA |
|---------------------------|--|-------|
| Normal                    |  | Koldt |
| PRODUKTANBEFALING 1       |  |       |
| <b>Gear Oil Alcat 10W</b> |  |       |

Kontroller alle 3 måneder/ 500 timer, skift alle 6 måneder/ 1000 timer

# CATERPILLAR MOTORDREVNE VEJHØVLE

## 24M B9K (2006 OG EFTER)



**GEAR Powershift**  
Kapacitet: 87 liter

ANVEND  
Normal

KLIMA  
Middelhavsagtigt

PRODUKTANBEFALING 1

**Gear Oil Alcat 30**

PRODUKTANBEFALING 2

**Gear Oil Alcat 50**

*Kontroller alle 10 timer, skift alle 6 måneder/ 1000 timer*

ANVEND  
Normal

KLIMA  
Koldt

PRODUKTANBEFALING 1

**Gear Oil Alcat 10W**

*Kontroller alle 10 timer, skift alle 6 måneder/ 1000 timer*

**TANDEMREVE**

Kapacitet: 322 liter (hver side)

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Gear Oil Alcat 30**

PRODUKTANBEFALING 2

**Gear Oil Alcat 50**

*Kontroller alle 1 måneder/ 100 timer, skift alle 24 måneder/ 2000 timer*

ANVEND  
Normal

KLIMA  
Arktisk

PRODUKTANBEFALING 1

**Gear Oil Alcat 10W**

*Kontroller alle 1 måneder/ 100 timer, skift alle 24 måneder/ 2000 timer*

# CATERPILLAR MOTORDREVNE VEJHØVLE

## 24M B9K (2006 OG EFTER)



### HYDRAULISK SYSTEM

Kapacitet: 142 liter (Hydrauliktank)

| ANVEND                        |                               | KLIMA                    |
|-------------------------------|-------------------------------|--------------------------|
| Normal                        |                               | Tropisk                  |
| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2           | PRODUKTANBEFALING 3      |
| <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> | <b>Gear Oil Alcat 30</b> |

Kontroller alle 100 timer, skift alle 12 måneder/ 2000 timer

| ANVEND                   |                             | KLIMA               |
|--------------------------|-----------------------------|---------------------|
| Normal                   |                             | Middelhavsagtigt    |
| PRODUKTANBEFALING 1      | PRODUKTANBEFALING 2         | PRODUKTANBEFALING 3 |
| <b>Agrifluid HT-Plus</b> | <b>Kroontrak MTH 10W-30</b> | <b>Agrifluid HT</b> |

Kontroller alle 100 timer, skift alle 12 måneder/ 2000 timer

| ANVEND                    |  | KLIMA   |
|---------------------------|--|---------|
| Normal                    |  | Moderat |
| PRODUKTANBEFALING 1       |  |         |
| <b>Gear Oil Alcat 10W</b> |  |         |

Kontroller alle 100 timer, skift alle 12 måneder/ 2000 timer

### HJULSPINDELLEJE FOR

Kapacitet: 4 liter (hvert hjul)

| ANVEND                   |                          | KLIMA   |
|--------------------------|--------------------------|---------|
| Normal                   |                          | Moderat |
| PRODUKTANBEFALING 1      | PRODUKTANBEFALING 2      |         |
| <b>Gear Oil Alcat 30</b> | <b>Gear Oil Alcat 50</b> |         |

Kontroller alle 3 måneder/ 500 timer, skift alle 24 måneder/ 2000 timer

| ANVEND                    |  | KLIMA   |
|---------------------------|--|---------|
| Normal                    |  | Arktisk |
| PRODUKTANBEFALING 1       |  |         |
| <b>Gear Oil Alcat 10W</b> |  |         |

Kontroller alle 3 måneder/ 500 timer, skift alle 24 måneder/ 2000 timer

### KØLESYSTEM

Kapacitet: 87 liter

| ANVEND               |  | KLIMA   |
|----------------------|--|---------|
| Normal               |  | Moderat |
| PRODUKTANBEFALING 1  |  |         |
| <b>Coolant SP 17</b> |  |         |

Kontroller alle 10 timer, skift alle 72 måneder/ 12000 timer

# CATERPILLAR MOTORDREVNE VEJHØVLE 24M B9K (2006 OG EFTER)



## DRIVEGEARKASSE

Kapacitet: 8,5 liter (hvert)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*