

CATERPILLAR TELESKOPLÆSSER RT/TH TH336C (75 KW, C3.4B) MJR/THM S/N 00150 -> (2012 OG EFTER)



MOTOR C3.4B
Kapacitet: 8 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1

Dieselfleet MSP 15W-40

Kontroller alle 10 timer, skift alle 500 timer

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra FE 5W-30

PRODUKTANBEFALING 2

Agrisynth LSP Ultra 10W-40

PRODUKTANBEFALING 3

Agrisynth MSP 10W-40

Kontroller alle 10 timer, skift alle 500 timer

DIFFERENTIALE BAG
Kapacitet: 11,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 30

Kontroller alle 250 timer, skift alle 1000 timer

ANVEND
Første Service

KLIMA
Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 30

Kontroller alle 50 timer, skift alle 250 timer

DIFFERENTIALE FOR
Kapacitet: 10,5 liter, Kapacitet: 0,35 liter (specialadditiv)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

CATERPILLAR TELESKOPLÆSSER RT/TH TH336C (75 KW, C3.4B) MJR/THM S/N 00150 -> (2012 OG EFTER)



GEAR Powershift
Kapacitet: 14 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Gear Oil Alcat 30

PRODUKTANBEFALING 2
Gear Oil Alcat 50

Kontroller alle 10 timer, skift alle 1000 timer

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gear Oil Alcat 10W

Kontroller alle 10 timer, skift alle 1000 timer

ANVEND
Første Service

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Gear Oil Alcat 30

PRODUKTANBEFALING 2
Gear Oil Alcat 50

Kontroller alle 10 timer, skift alle 250 timer

ANVEND
Første Service

KLIMA
Moderat

PRODUKTANBEFALING 1
Gear Oil Alcat 10W

Kontroller alle 10 timer, skift alle 250 timer

NAVREDUKTIONER
Kapacitet: 0,8 liter (Alle)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gear Oil Alcat 30

Kontroller alle 250 timer, skift alle 1000 timer

ANVEND
Første Service

KLIMA
Moderat

PRODUKTANBEFALING 1
Gear Oil Alcat 30

Kontroller alle 50 timer, skift alle 250 timer

CATERPILLAR TELESKOPLÆSSER RT/TH TH336C (75 KW, C3.4B) MJR/THM S/N 00150 -> (2012 OG EFTER)



REDUKTIONSGEARKASSE

Kapacitet: 2,8 liter

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Kontroller alle 250 timer, skift alle 1000 timer

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gear Oil Alcat 10W		

Kontroller alle 250 timer, skift alle 1000 timer

ANVEND		KLIMA
Første Service		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Skift alle 250 timer

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1		
Gear Oil Alcat 10W		

Skift alle 250 timer

HYDRAULISK SYSTEM

Kapacitet: 90 liter (Hydrauliktank), Kapacitet: 135 liter (Total)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

SMØREPUNKTER/-NIPLER DRIVAKSEL

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
HT Q9 High Grade Grease		

Kontroller alle 500 timer

CATERPILLAR TELESKOPLÆSSER RT/TH TH336C (75 KW, C3.4B) MJR/THM S/N 00150 -> (2012 OG EFTER)



SMØREPUNKTER/NIPLER ANDRE

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

HT Q9 High Grade Grease

Kontroller alle 50 timer

SMØREPUNKTER/NIPLER GLIDENDE OVERFLADER PÅ BOM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

HT Q9 High Grade Grease

Kontroller alle 50 timer

KØLESYSTEM

Kapacitet: 16 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 17

Kontroller alle 10 timer, skift alle 72 måneder/ 12000 timer

KLIMAANLÆGSSYSTEM

Kapacitet: 1,35 kg

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.