

CATERPILLAR TRÆFÆLDNINGSBUNCHER

552 SERIE 2 F7G (2012 OG EFTER)



MOTOR C9 Acert
Kapacitet: 39 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 1 måneder/ 250 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP 10W-40	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Kontroller alle 10 timer, skift alle 1 måneder/ 250 timer

HYDRAULISK MOTORHJELMHOLDESYSTEM
Kapacitet: 3,8 liter (Hydrauliktank)

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Multifleet SCD 30	Gear Oil Alcat 30

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30

HYDRAULISK SYSTEM
Kapacitet: 318 liter (Hydrauliktank)

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Multifleet SCD 30	Gear Oil Alcat 30

Kontroller alle 10 timer, skift alle 6 måneder/ 1000 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Kontroller alle 10 timer, skift alle 6 måneder/ 1000 timer

CATERPILLAR TRÆFÆLDNINGSBUNCHER

552 SERIE 2 F7G (2012 OG EFTER)



SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

HT Q9 High Grade Grease

PRODUKTANBEFALING 2

Labora Grease

PRODUKTANBEFALING 3

MoS2 Grease EP 2

KØLESYSTEM

Kapacitet: 36 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 17

Skift alle 12000 timer/ 72 måneder

DREJEGEAR

Kapacitet: 21,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

HT Q9 High Grade Grease

PRODUKTANBEFALING 2

Labora Grease

PRODUKTANBEFALING 3

MoS2 Grease EP 2

Kontroller alle 1 måneder/ 250 timer

CATERPILLAR TRÆFÆLDNINGSBUNCHER

552 SERIE 2 F7G (2012 OG EFTER)



KØREREDUKTIONSENHED

Kapacitet: 6 liter (hvert)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

ANVEND		KLIMA
Normal		Arktisk
PRODUKTANBEFALING 1		
Gear Oil Alcat 10W		

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

ANVEND		KLIMA
Væskeanalyse		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Kontroller alle 500 timer

ANVEND		KLIMA
Væskeanalyse		Arktisk
PRODUKTANBEFALING 1		
Gear Oil Alcat 10W		

Kontroller alle 500 timer

NAV VARIABEL BLÆSER

Kapacitet: 0,65-1,22 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

CATERPILLAR TRÆFÆLDNINGSBUNCHER

552 SERIE 2 F7G (2012 OG EFTER)


SVINGREDUKTIONSENHED

Kapacitet: 10 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Kontroller alle 10 timer, skift alle 6 måneder/ 1000 timer

ANVEND		KLIMA
Normal		Arktisk
PRODUKTANBEFALING 1		
Gear Oil Alcat 10W		

Kontroller alle 10 timer, skift alle 6 måneder/ 1000 timer

ANVEND		KLIMA
Væskeanalyse		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Kontroller alle 250 timer

ANVEND		KLIMA
Væskeanalyse		Arktisk
PRODUKTANBEFALING 1		
Gear Oil Alcat 10W		

Kontroller alle 250 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.