

CATERPILLAR TRÆFÆLDNINGSBUNCHER TK370 WBD



MOTOR 3126
Kapacitet: 31 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2
Synfleet SHPD 10W-40

PRODUKTANBEFALING 3
Dieselfleet CD+ 15W-40

Kontroller alle 10 timer, skift alle 1 måneder/ 250 timer

DIFFERENTIALE BAG
Kapacitet: 52 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Gear Oil Alcat 50

Kontroller alle 500 timer, skift alle 12 måneder/ 2000 timer

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gear Oil Alcat 30

Kontroller alle 500 timer, skift alle 12 måneder/ 2000 timer

ANVEND
Normal

KLIMA
Arktisk

PRODUKTANBEFALING 1
Gear Oil Alcat 10W

Kontroller alle 500 timer, skift alle 12 måneder/ 2000 timer

CATERPILLAR TRÆFÆLDNINGSBUNCHER TK370 WBD



DIFFERENTIALE FOR

Kapacitet: 52 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gear Oil Alcat 50

Kontroller alle 50 timer, skift alle 12 måneder/ 2000 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 30

Kontroller alle 50 timer, skift alle 12 måneder/ 2000 timer

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

Gear Oil Alcat 10W

Kontroller alle 50 timer, skift alle 12 måneder/ 2000 timer

GEAR

Kapacitet: 3,8 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

HYDRAULISK SYSTEM

Kapacitet: 300 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gear Oil Alcat 10W

PRODUKTANBEFALING 2

Gear Oil Alcat 30

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

KØLESYSTEM

Kapacitet: 45 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 17

Kontroller alle 10 timer, skift alle 72 måneder/ 12000 timer

CATERPILLAR TRÆFÆLDNINGSBUNCHER TK370 WBD



PUMPEDREV

Kapacitet: 3,8 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.