

CATERPILLAR VIBRATORY COMPACTORS CB/CC/CD/CP/CS CB-424 6LD, DEUTZ



MOTOR Deutz
Kapacitet: 9,5 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Multifleet SCD 40	Multifleet SCD 30

Kontroller alle 10 timer, skift alle 1 måneder/ 250 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Kontroller alle 10 timer, skift alle 1 måneder/ 250 timer

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1		
Multifleet SCD 10W		

Kontroller alle 10 timer, skift alle 1 måneder/ 250 timer

REDUKTIONSGEARKASSE
Kapacitet: 0,75 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140

Kontroller alle 10 timer, skift alle 3 måneder/ 500 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

Kontroller alle 10 timer, skift alle 3 måneder/ 500 timer

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	SP Gear 1071	

Kontroller alle 10 timer, skift alle 3 måneder/ 500 timer

CATERPILLAR VIBRATORY COMPACTORS CB/CC/CD/CP/CS CB-424 6LD, DEUTZ



HYDRAULISK SYSTEM

Kapacitet: 42 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 10W

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.